



Earthing Kits



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582



3M™ AC Series - Armour Continuity Kits

This Scotchcast™ Armour Continuity Kit is designed to provide complete electrical continuity across the joint position on 2, 3 or 4 core armoured power cables for inline, tee or branch configurations.

The AC kits contain two interlocking contact rings and two lengths of steel band with pre-assembled buckles. Used in conjunction with an ACC kit containing the required length of copper cord.

The JO20 'Pok-It' Tool is used to assemble the components and ensure low contact resistance.

ACCEPTED CABLE DIAMETER		
KIT	MAX	MIN
AC-1	13	8
AC-2	19	13.1
AC-3	25	19.1
AC-4	32	25.1
AC-5	38	32.1
AC-6	44	38.1
AC- 7	48	44.1
AC-8	54	48.1
AC-9	60	54.1
AC-10	70	60.1

COPPER CORD LENGTH	
KIT	Mm
ACC-21	180
ACC-22	230
ACC-23	350
ACC-24	950
ACC-25	1300
ACC-26	2300



Band it Pok it Tool

Pok-It II Tool J020 is a lightweight pocket sized tool for use with 3M AC Series Kit. Applies tension and includes built-in cutter. Weight 1.1lbs (.5kg).



3M™ Constant Force Springs

Scotchcast™ Constant Force Springs are a range of solderless connections for use on lead or aluminium sheaths and copper screened cables.

The springs are easily applied by rolling onto the sheath connections, whereupon it continues to exert a constant pressure.

PART NUMBER	INNER DIAMETER OF SPRING	SPRING WIDTH	SPRING TAPE LENGTH (Mm)	MIN DIA	MAX DIA
P59	3.5	9	80	4	10
P60	7.5	10	175	9	15
P61	11	16	225	14	22
P62	14.5	16	295	18.5	29
P63	18.5	16	375	23.5	37
P64	25	16	505	31	50
P65	32	20	710	44	70
P66	44	20	935	58	94
P67	57	20	1250	70	110



3M™ Earth Bonding Kits SB 1 - SB4

Scotchcast™ Spring Bonding Kits may be used to bond the armour wires on armoured cables in 'Scotchcast' Cable jointing, including the 'resin pressure method' of jointing. The SB kits provide an electrical bond and should be used where earthing leakage protection is installed.

The SB Series contains two constant force springs; copper braid and insulating tape and can be applied without the aid of special tools.

KIT	ACCEPTED CABLE DIAMETER (Mm)	LENGTH OF COPPER CORD	
	MAX	MIN	MIN
SB1	12	9	200
SB2	19	14	250
SB3	25	23.5	320
SB4	38	31	350



Size

25mm x 4.5m

Scotch® 24 Electrical Shielding Braid

Scotch® 24 Electrical Shielding Tape is an all metal, open-weave, shielding braid tape in a flat, cable like form. It is conformable due to the open-weave knit construction of two No.36 AWG tinned copper wires. Tape thickness is 0.406mm.

Features

- Tinned copper conductors
- Stable at elevated temperatures
- Oil resistant
- Compatible with power cable insulations
- Fire resistant
- Elongates easily to conform to inclined or uneven surfaces
- Corrosion resistant
- Compatible with all high-voltage splicing and terminating materials
- Unaffected by solvents, UV, ozone, and moisture
- Suitable for indoor and outdoor applications

Applications

- To provide shielding for cable joints on shielded power cables
- To make the conductive portion of the stress cone on power cable terminations
- To smooth connector area in oil-filled cables



Size

25mm x 4.5m

Scotch® 25 Electrical Grounding Braid

Scotch® 25 Electrical Grounding Braid is an all-metal woven grounding braid in a flat, cable-like form. It is conformable due to its woven construction of 240 strands of #30 AWG tinned copper wires. Tape thickness is 2.38mm. Cross sectional area 16mm².

Features

- High current-carrying capacity
- Tinned copper wires
- Stable at elevated temperatures
- Oil resistant
- Compatible with all power cable installations
- Fire resistant
- Easy conformity to irregular surfaces
- Corrosion resistant
- Compatible with high-voltage jointing and termination materials
- Unaffected by solvents, ultra-violet, ozone, and moisture
- Usable for indoor and outdoor applications
- Can be easily soldered to high-voltage cable shields

Applications

- To provide a fault current path across shielded cable joints
- For grounding high-voltage joints, terminations, cables or other cable accessories



3M™ Copper braid

3M supply a range of copper braid to be used as an earthing & grounding accessory for joints and terminations.

Available in a continuous roll of 3/8" flat copper braid, or in cut pieces of Tinned Copper Hose.

Applications

- To provide earth continuity and fault current path across shielded low voltage cable joints
- For grounding joints, terminations, cables, or other cable accessories

Range Available	
Flat Braid	3/8" x 100m (4mm²)
Tinned Cu Hose	16mm² x 300mm
Tinned Cu Hose	25mm² x 400mm
Tinned Cu Hose	50mm² x 450mm
Tinned Cu Hose	95mm² x 600mm



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

Electrical Tapes
Low Voltage Joints & Terminations
Cold Shrink tubes & End Caps
Earthing Kits
Resins
Medium Voltage Joints & Terminations
Hazard Area Joint & Termination Kits
Cable & Wire Management
Lugs & Connectors
Heat Shrink
Cable & Fault Locators & Electronic Marker Systems