




Electrical Tapes

3M offer a range of over 30 electrical tapes and mastics for insulation, jointing, corrosion protection, all weather protection and environmental sealing. From Scotch®

33+ Vinyl tape to Scotch® 130C Linerless rubber splicing tape to Scotch® 2200 Mastic pads, 3M Electrical Tapes provide exceptional performance and reliability.



PVC Insulating Tape



Scotch® Super 33+ High Quality PVC

Scotch® Super 33+ Electrical Tape is a premium grade, 0.178mm thick, all-weather vinyl insulating tape. It is designed to perform continuously in ambient temperatures of up to 105°C (220°F). The tape is conformable, and suitable for cold weather applications down to -18°C (0°F). The combination of elastic backing and aggressive adhesive provides moisture-tight electrical and mechanical protection with minimum bulk.

Features

Excellent resistance to abrasion, moisture, alkalis, acids, corrosion and varying weather conditions (including ultraviolet exposure)

Flame retardant

Conforms to BS 3924 and UL510

Applications

Primary electrical insulation for all wire and cable splices rated up to 600V and 105°C

Size	Colour
19mm x 20m	Black



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775882



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775882



Sizes

19mm x 20m
25mm x 33m
38mm x 33m

Scotch® Super 88 - All Weather PVC Tape

Scotch® Super 88 Electrical Tape is a premium grade, 0.216mm thick, all-weather vinyl insulating tape. It has excellent resistance to abrasion, moisture, alkalis, acids, corrosion and varying weather conditions (including ultraviolet exposure). The combination of elastic backing and aggressive adhesive provides moisture-tight electrical and mechanical protection with minimum bulk.

Features

- Designed to perform continuously in ambient temperatures of up to 105°C (220°F) and conformable for cold weather applications down to -18°C (0°F)
- Good elongation for excellent conformability to irregular surfaces
- Flame retardant
- Excellent abrasion and puncture resistance
- Meets BS 3924 and UL 510

Applications

Primary electrical insulation (especially at low temperatures) for harnessing all wires and cable joints up to 600 volts and 105°C



Sizes Colours

Sizes	Colours
19mm x 20m	Red
19mm x 20m	Blue
19mm x 20m	Brown
19mm x 20m	Yellow
19mm x 20m	White

Scotch® 35 Tape - Colour Coding PVC

Scotch® 35 Vinyl Electrical Colour Coding Tape is an electrical grade, 0.178mm thick PVC tape with a pressure sensitive rubber adhesive, available in nine fade resistant colours.

Features

- Abrasion and weather resistant, excellent electrical insulating properties, wraps smoothly, conforms well and holds over a wide range of temperatures (0°C to 80°C)
- Resistant to moisture, alkalis, acids, U.V and corrosion
- Conforms to BS 3924 and UL 510

Applications

Scotch 35 Tape is designed for use in phase identification, Colour coding of motor leads and piping systems, and for marking safety areas
Joint, Termination and Connector insulation up to 600V



Sizes

12mm x 33m
19mm x 33m
25mm x 33m
38mm x 33m
50mm x 33m

Scotch® 22 Tape - Heavy Duty PVC

Scotch® 22 Electrical Tape is a premium grade, 0.254mm thick, vinyl insulating tape. It is designed to perform continuously in ambient temperatures up to 80°C (176°F). The tape is conformable, and suitable for cold weather applications down to -10°C (15°F). It has excellent resistance to abrasion, moisture, alkalis, acids, corrosion and varying weather conditions (including ultraviolet exposure).

Features

- High elastic memory
- Flame retardant
- Temperature rating from -10°C to 80°C
- High resistance to corrosion, U.V, moisture and chemicals
- Conforms to BS 3924 and UL 510

Application

Suitable for all heavy-duty applications, including bus bar insulations, harnessing, cable sheath repair and sealing connectors

**Sizes**

9mm x 33m
12.7mm x 33m
19mm x 33m
25mm x 33m
38mm x 33m
50mm x 33m

Scotch® 33 Tape - General Purpose PVC

Scotch® 33 Electrical Tape is a quality, 0.178mm thick, general-purpose vinyl insulating tape. It has excellent resistance to abrasion, moisture, alkalis, acid, copper corrosion and varying weather conditions (including sunlight). It is a polyvinyl chloride (PVC) tape that has a high dielectric strength, is flame retardant and conformable, and provides excellent mechanical protection with minimum bulk.

Features

- Flame retardant
- Wraps and conforms easily
- Forms a protective jacket (excellent abrasion resistance for high voltage cable joints and terminations)
- Conforms to BS 3924 and UL510

Applications

The tape is designed to perform in a continuous operating temperature up to 80°C
Indoor or outdoor insulations (especially in moisture and solvent vapour areas) for all general purposes wiring applications and cable joints up to 600V

**Sizes**

19mm x 20m

Scotch® 780 - PVC Electrical Tape

Scotch® 780 Electrical Tape is a good quality, 0.178mm thick, medium purpose PVC insulating tape.

It is a polyvinyl chloride (PVC) tape that has a high dielectric strength, is conformable and provides very good mechanical protection with minimum bulk.

Features

Excellent resistance to abrasion, moisture, alkalis, acid and varying weather conditions (including sunlight)

Flame retardant

Applications

- Primary electrical insulation for all wire and cable joints and repairs.
- Harnessing of wire and cables.
- Indoor and outdoor applications at temperatures from -10°C to +80°C.

**Sizes**

19mm x 25m

Temflex™ 1500 – PVC Electrical Tape

Temflex™ 1500 Electrical Tape is a good quality, 0.15mm thick, general-purpose PVC insulating tape. Available colours are: black, blue, brown, yellow, yellow/green, grey, orange, red, white, and green.

Features

- Good resistance to abrasion, moisture, alkalis, acid and varying weather conditions (including sunlight)
- High dielectric strength, conformable and provides good mechanical protection with minimum bulk
- Meets requirements of IEC 60454-3-1-5/F-PVCP/90 and has VDE Marks Licence

Applications

- Primary electrical insulation for all wire and cable joints and repairs
- Harnessing of wire and cables
- For indoor and outdoor applications

Self Amalgamating, Insulating and Splicing Tape

Scotch® 23 Tape - Premium Grade Self Bonding Rubber



Sizes

19mm x 9.15m
25mm x 9.15m
38mm x 9.15m
50mm x 9.15m

Scotch® 23 Electrical Tape is a highly conformable 0.76mm thick, self amalgamating EPR (Ethylene Propylene Rubber) based, high voltage jointing tape. It is non-vulcanising and shelf-stable with excellent electrical properties. 23 Tape can be used as insulation for low voltage applications as well as insulation for joints up to 69kV.

Features

- Physical and electrical properties are unaffected by the degree of stretch
- Can be stretched up to 100% to give void-free, moisture-resistant insulation
- Self-al amalgamating tape
- Excellent electrical properties

Application

- Primary insulation for building stress cones on cables up to 35kV
- Primary electrical insulation for cable jointing and terminating up to 69kV with up to 90°C continuous operating temperatures and 130°C emergency overload temperature



Sizes

19mm x 9m
25mm x 9m
38mm x 9m
50mm x 9m

Scotch® 130C Linerless Self Bonding Tape – EPR

Scotch® 130C Electrical Tape is a highly conformable, 0.762mm thick, linerless self amalgamating EPR (Ethylene Propylene Rubber) based, high voltage insulating tape formulated to provide excellent thermal dissipation of splice heat. The tape is designed for use in splicing and terminating wires and cables.

Features

- Non-vulcanizing and highly conformable
- U.V, weather and corona resistant
- Flame retardant
- Self-al amalgamating tape

Applications

- Primary electrical insulation for cable jointing and terminating up to 69kV with up to 90°C continuous operating temperatures and 130°C emergency overload temperature
- Moisture sealing electrical connections
- Bus bar insulations
- End sealing high-voltage cables

Sizes

19mm x 9.15m

Temflex™ 2151 Economy Grade Self Bonding Rubber -

Temflex™ 2151 Electrical tape is a highly conformable, 0.51mm Thick, self-fusing EPR (Ethylene Propylene Rubber) based low voltage jointing tape.



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

Self Amalgamating, Insulating and Splicing Tape



Sizes

25mm x 9m

Scotch® 70 - Silicone Rubber Tape

Scotch® 70 Silicone Rubber Electrical Tape is a 0.3mm thick, high temperature arc-and track-resistant tape composed of self-fusing, inorganic silicone rubber, with easy-tear and easy-strip liner.

Features

- Excellent track resistance
- Excellent arc resistance
- Excellent ozone resistance
- High dielectric strength
- Glass "H" material (180 °C continuous operation)
- Workable in extremely low temperatures
- Excellent conformability
- Excellent instantaneous fusion; does not need to be held down

Applications

As an Over-wrap for protection of terminating high-voltage cables against arcing and tracking



Sizes

19mm x 4.5m

Scotch® 13 Tape - Semi Conducting EPR

The soft, black rubber tape is a 0.762mm thick, highly conformable, semi-conducting EPR (Ethylene Propylene Rubber) based high-voltage splicing tape. It is non-vulcanising and shelf stable, with stable conductivity over a wide temperature range. Its conductivity is not affected, except by low-viscosity oils. The conductivity of cable semi-conducting jackets is not affected by 13 Tape.

Features

- Remains stable at 130°C and is non-vulcanising
- Elongates easily to form irregular shapes
- Resist cracking, solvents, U.V and moisture
- Tape and liner boldly printed to distinguish from insulating tape
- Meets requirements of ADTM-D4388, Type IV

Application

- Electrically rounds-off high voltage connectors and lugs
- Provides screen continuation for high voltage joints and terminations
- Replaces semi-conducting layer beneath metallic shield of damaged cables
- Forms conductive portion of stress cones



Sizes

19mm x 4.5m

Scotch® 2220 - Stress Control Tape

0.762mm thick, mastic tape, for stress control applications in joints and terminations at all voltages.

Features

- Temperature rating: 90°C continuous operating with emergency overload temperature of 130°C
- Changes voltage distribution in the electrical field surrounding a high voltage termination or joint.
- Reduces stress concentration to values found in continuous cables

Applications

Provides stress relief for all cable terminations and high voltage joints

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS



11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582



Sizes (2210 Tape)

19mm x 6m

38mm x 6m

Backing and Mastic:

* Thickness 0.815mm (19x38mm rolls)

* Thickness 1.18mm (101mm rolls)

Sizes (2200 Pads)

114mm x 165mm

Backing and Mastic:

* Thickness 3.2mm

Scotch® 2210 - Vinyl Mastic Tape

Scotch® 2200 Vinyl Mastic Pads

Scotch® Tape VM 2210 and 2200 Pads are self-fusing, rubber based insulating compounds, laminated to a flexible, all-weather grade vinyl (PVC) backing. These products are designed to insulate and moisture-seal all connections up to 600 volts, and have excellent resistance to abrasion, moisture, alkalis, acid, copper corrosion and varying weather conditions (including sunlight).

Features

- Compatible Rubber Mastic
- Flexible over wide range of temperatures
- Highly resistant to ultraviolet light
- Usable for indoor or outdoor applications

Applications (600V maximum)

- Bolted connections
- Service drops
- Traffic signal wire connections
- Lighting connections
- Transformer bushing protection



Size

50mm x 3.03m

Scotch® 2228 - Rubber Mastic Tape (EPR)

Scotch® 2228 is a 1.65mm thick, conformable self-fusing rubber electrical insulating and sealing tape. Scotch® 2228 consists of an EPR (ethylene propylene) backing coated with aggressive, temperature-stable mastic adhesive. It is designed for electrical insulating and moisture sealing applications.

Features

- Conformable for application over irregular surfaces
- Compatible with solid dielectric cable insulations
- Self-fusing tape
- Flexible over wide temperature range
- Excellent weather and moisture resistance
- Excellent adhesion and sealing characteristics with copper, aluminium and power cable jacket materials

Applications

- Primary electrical insulation for cable and wire connections rated up to 1000 volts
- Primary electrical insulation for bus bar connections rated up to 35kV



Size

19mm x 1.5m

Scotch® 2221 - Mastic Tape

Scotch® 2221 Tape provides excellent oil barrier and shows good stress control characteristics. It is a 1.5mm thick, soft, self-fusing, oil resistant, elastomeric PU mastic tape on a liner for medium voltage applications.

Features

- Good stress control
- Oil resistant

Applications

- Scotch® 2221 Tape is designed for use in oil barrier applications in paper, insulated MV cable joints and terminations

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582



**Size**

95mm x 3.08m

Scotch® 2229 - Mastic Tape

Scotch-Seal™ 2229 Mastic Tape is a 3.2mm thick, conformable, durable, tacky mastic coated on an easy release liner.

The product is designed for quick and easy insulating, padding and sealing of objects that need to be protected from adverse environmental conditions. It is well suited for corrosion protection.

Features

Excellent adhesion and sealing characteristics to metals, rubbers, synthetic cable insulations and jackets

Wide temperature stability while maintaining its sealing properties. (-34°C to 71°C)

Conformable and moldable for easy applications over irregular surfaces

Does not crack when subjected to repeated flexing

Retains its flexibility at low temperatures resulting in ease of application and continuous performance at reduced temperatures

Applications

For sealing high voltage cable splice and termination accessories

For insulating electrical connections rated up to 1000 volts if over wrapped with vinyl or rubber electrical tape

For padding irregular shaped connections

For providing corrosion protection to a wide variety of electrical connections and applications

For sealing ducts and cable end seals

For sealing against dust, soil, water and other environmental conditions

**Size**

38mm x 1.5m

Scotchfil™ - Electrical Insulation Putty

Scotchfil™ Electrical insulation putty is a 3.175mm thick electrical grade compound in tape form. It is UL Recognised as a joint insulation for electrical conductors at temperatures up to 80°C (176°F) when over wrapped with either Super 33+ or Super 88 Vinyl Electrical Tape.

Features

Non-corrosive, synthetic rubber

Excellent ageing properties

Applies cleanly without waste

Excellent electrical properties

Will not dry out

Applications

To insulate low-voltage (600 volts and less) connections

To build up cable joints and fill out major irregularities and voids in low-voltage joints (2300 volts and less) in order to obtain a uniform base for further taping

To round out high-voltage connections to gear

To smooth bus bar irregularities

To create a resin dam in resin pressure joints

To create a moisture seal at ground wire exit in high-voltage joints

To moisture seal multi-conductor cable connections

**Size**

20mm x 10m

Colour

Black

Scotch-Seal™ - 5313 Preformed Sealant Strip

5313 is a tacky solid extrusion based on a synthetic rubber. High adhesive strength – sufficient to cause cohesive failure of the sealer before loss of adhesion to the substrate, when pulled with tension. The sealer is a non-curing type and retains the same properties and consistency after ageing in several different environments, including weathering.

Features

High adhesive strength

Excellent water / weathering resistance

Ozone resistant

Service temperature range -29°C to 135°C

Application

Sealing applications in conjunction with 3M Cable Joints

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582





Size
50mm x 46m

Scotch® 2000 - Duct Tape

Scotch® 2000 Electrician's Duct Tape is a 0.152mm thick, water resistant duct tape with polyvinyl chloride (PVC) backing and a rubber adhesive.

Note: This tape is not recommended for sealing air ducts

Features

- Easy tear
- No cloth – does not absorb water
- Clean removal (minimal residue)

Applications

Scotch 2000 is designed to be an electrician's utility tape for holding and bundling applications.

Marking Tapes



Scotch® 9545 Cloth Tape - Pre-printed Phase Marking

Scotch® 9545 is a heavy-duty cloth tape, pre-printed with phase marking identification characters. The tape has either a yellow or white background, with black printing. Rolls are 19mm x 10m Suitable for identification of electrical wires and cables. Tape thickness 0.27mm

Features

Banding – a good adhesive and non-stretch strength for a reliable grip

Applications

to assist in cable identification

Yellow	
Printed Character	Part Number
L1	SL1-R
L2	SL2-R
L3	SL3-R
N	SN-R
L	SL-R
White	
L1	SL1-RW
L2	SL2-RW
L3	SL3-RW
N	SN-RW
L	SL-RW



Temflex™ 1700P Pre-printed Phase Marking Tape – PVC

Temflex™ PVC pre-printed with phase marking identification characters. The tape has a white background with black printing. Rolls are 15mm x 10m x 0.77mm

Features

- Flame retardant
- Operating temperature range - 10°C to 80°C

Applications

To assist cable identification

White	
Printed Character	Part Number
L	T1700PL
L1	T1700PL1
L2	T1700PL2
L3	T1700PL3
N	T1700PN

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582



**Sizes**

50 Tape (1)	51 Tape (2)
25mm x 30.5m	25mm x 30.5m
50mm x 30.5m	50mm x 30.5m
101mm x 30.5m	101mm x 30.5m
152mm x 30.5m	101mm x 30.5m

(1) Thickness 0.254mm

(2) Thickness 0.508mm

Scotchrap™ 50 and 51 Tape - All Weather Corrosion Protection

Scotchrap™ 50 and 51 Tapes are tough, PVC (polyvinyl chloride) based tapes with special high tack adhesives formulated to resist corrosion of metal piping systems above and below ground, fittings and joints on all millcoated pipe and electrical conduit systems.

Features

Resists abrasion, moisture, corrosive salt water, soil acids, and alkalis and salts

Resistant to common chemicals, chemical vapours

Resistant to outdoor weathering and sunlight

Resistant to impact, abrasion, punctures and tears

Both tapes have high electric strength, and excellent insulating properties.

Continuous operating temperature range from -48°C to 80°C

Application temperature from -12°C to 65.6°C

Applications

Protection of metal pipe systems both above and below ground.

Use Scotchrap Pipe primer to prepare surfaces for tape application

Use Scotchfil Electrical Insulation putty* to build up irregular surfaces to provide a smooth, waterproof taping surface

*For information on Scotchfil Electrical Insulating Putty, see page 14

**Sizes**

38mm x 6m
76mm x 6m

Scotch® 77 - Arc & Fire Proofing Tape

Scotch® 77 Tape is a 0.762mm thick, arc and fireproofing tape designed to protect all types of electrical cables. Its unique formulation allows the manufacture of an unsupported elastomer that expands in fire to provide a thick char build-up between the flame and cable. This insulating fire wall acts as a heat shield and flame barrier, thus protecting the cables and accessories.

Features

Clean and easy to apply

Provides fault arc protection to adjacent wrapped cables

Provides additional electrical insulation

Resists U.V., water, salt water, acids and sewage

Applications

To fire and arc proof high-energy power cables where exposed to failures of other high-energy cables (any cables within 45cm are considered to be exposed)

To fire and arc proof control cables when high energy power cables are present

To fire and arc proof all cables in areas where possibility of fire hazard exists

To provide additional electrical insulation, thus reducing possibilities of transferred arcs

To fire and arc proof piping systems (ie. gas, water, or oil lines)

The installed tape to be secured with 2 layers of 69 glass cloth tape



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 977 5582



Scotch® 27 Tape - Glass Cloth

Scotch® 27 Tape is a 0.178mm thick, woven glass cloth tape designed to operate in applications requiring high mechanical strength and resistance to high temperatures. The glass cloth is specially treated and prepared to provide corrosion free protection. The adhesive is a rubber pressure-sensitive thermosetting system.

Features

The glass will not shrink, rot or burn and has a high tensile strength
The tape is designed for continuous use at class "B" (130°C) temperature with a high temperature thermosetting adhesive

Applications

Useful applications include a heat-stable insulation for furnace and oven controls, motor leads and switches

Size	Colour
12mm x 20m	White



Scotch® 69 Tape - Glass Cloth Printable Film / Silicone Adhesive

69 Glass Cloth Electrical Tape is a 0.177mm thick, white glass cloth tape with a high-temperature thermosetting silicone adhesive. The thermosetting adhesive provides an increased bond once applied in areas of high ambient temperatures.

Features

69 Tape is UL recognized for continuous use up to 180°C
Meets requirements of Military Specification No. MIL-I-19166C

Applications

Insulating electric and induction type furnace power supply leads
Securing high temperature, non-PSA insulations (such as asbestos and glass) in high temperature areas
To be used in conjunction with 77 Tape* for arc and fire proofing applications

*For information on 77 Tape, see page 16

Sizes	Colour
6mm x 33m	White
9mm x 33m	White
12mm x 33m	White
15mm x 33m	White
19mm x 33m	White
25mm x 33m	White
38mm x 33m	White
50mm x 33m	White



Scotch® 2510 - Cambric Tape

Scotch® Varnished Cambric Tape is made from straight-cut woven cotton cambric fabric. The fabric is oil primed and coated with a high-grade yellow electrical insulating varnish.

The tape is flexible, electrically insulating and moisture resistant with a smooth finish.

Features

Designed to perform continuously in temperatures up to 105°C (220°F)
Excellent resistance to abrasion, puncture and cut-through.

Application

For insulating joints requiring rapid and clean re-entry
such as motor lead and service drop
Connections, heavy split bolts in raceways and bus bar insulating.

Sizes
19mm x 20m

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS


11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK
Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582



Electrical Tapes Selection Chart



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS

FURSE EARTHING

www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371

Tel 0044 117 977 4647 Fax 0044 117 9775582