




FIELD OF USE :

Arc flash protection of the face and the head (10 cal / cm²).

CHARACTERISTICS :

- **Face shield with chin cup**
 - 10 cal/cm² ATPV rating
 - In conformity with ASTM F2178
 - Absorbs >99,9% of harmful UV radiation
 - 70% light transmission
 - Resistant to fogging
- **ABS electrician Helmet MO-182/1-B**
 - ABS helmet, no ventilation, ultra light weight.
 - Low density – high pressure polyethylene head rim.
 - Deformable helmet in case of shock, equipped with a “gutter”.
 - Adjustable size from 53 to 62 cm, adjustment of head rim at 5 mm intervals.
 - 4 points textile head base, adjustable for a perfect fit.
 - Frontal trimming.
 - In compliance with the standards:
 - EN 397 :
Use at very low temperature: - 30°C.
Electrical insulation: 440 V AC; DIN EN 397 1 000 V.
Protection against ejections of molten metal (MM).
 - EN 50 365 1 000 V
 - ANSI Z 89.1:2003, Class E 20 000 V 
- **Delivered in a carrying bag for face shield and helmet M-87384**



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582