


- **Arc flash protective short coat**
 - 100 cal/cm² ATPV rating
 - In conformity with ASTM specifications F1959 and ASTM F1506
 - Made from arc flash resistant Kevlar / Nomex
 - Sewn with Nomex thread
 - FR components
 - Traditional thigh-length coat with a stand-up collar
 - Comfortable and generously cut
 - FR Velcro placket closure
 - FR knit wrists

- **Arc flash protective hood with face shield**
 - 100 cal/cm² ATPV rating
 - In conformity with ASTM specifications F2178 and the flammability requirements of ASTM F1506
 - VLT (Visual Light Transmission) = 26 %
 - Made from arc flash resistant Kevlar / Nomex
 - Sewn with Nomex thread
 - Anti-fogging replaceable lens

- **ABS electrician Helmet MO-182/1-B**
 - ABS helmet, no ventilation, ultra light weight.
 - Low density – high pressure polyethylene head rim.
 - Deformable helmet in case of shock, equipped with a “gutter”.
 - Adjustable size from 53 to 62 cm, adjustment of head rim at 5 mm intervals.
 - 4 points textile head base, adjustable for a perfect fit.
 - Frontal trimming.
 - In compliance with the standards :
 - EN 397 :
Use at very low temperature: - 30°C.
Electrical insulation: 440 V AC; DIN EN 397 1 000 V.
Protection against ejections of molten metal (MM).
 - EN 50 365 1 000 V
 - ANSI Z 89.1:2003, Class E 20 000 V 

- **Safety glasses MO-11000**
 - Protection against UV radiation and ejections of solid particles
 - Complies with the standard EN166
 - Optic class 1
 - Impact resistance level : F (steel ball 6mm at 45m/s)
 - Treatment anti-impact and anti-chemical product



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582