

Ball-Lok Ties

- In 316 and 304 Stainless Steel
- Self locking for speedy application
- Smooth Internal Diameter
- Install by hand or with K502, KE922 tools



304 Stainless Steel Package Quantity 100



Uncoated

| Cat. No. | Maximum Bundle Diameter | | Approximate Length | | Approximate Width | | Approximate Weight | | Min. Loop Tensile Strength | |
|----------|-------------------------|-----|--------------------|------|-------------------|-----|--------------------|------|----------------------------|------|
| | in | mm | in | mm | in | mm | Lbs. | Kg. | Lbs | N |
| KE1128 | 2.0 | 50 | 7.9 | 201 | 0.18 | 4.6 | 0.57 | 0.26 | 100 | 445 |
| KE1138 | 2.7 | 69 | 10.2 | 259 | 0.18 | 4.6 | 0.70 | 0.32 | 100 | 445 |
| KE1148 | 4.0 | 102 | 14.2 | 360 | 0.18 | 4.6 | 0.92 | 0.42 | 100 | 445 |
| KE1158 | 6.0 | 152 | 20.4 | 520 | 0.18 | 4.6 | 1.32 | 0.60 | 100 | 445 |
| KE1168 | 8.0 | 203 | 26.8 | 679 | 0.18 | 4.6 | 1.76 | 0.80 | 100 | 445 |
| KE1178 | 10.0 | 254 | 33.0 | 838 | 0.18 | 4.6 | 2.07 | 0.94 | 100 | 445 |
| KE1188 | 12.0 | 305 | 42.0 | 1067 | 0.18 | 4.6 | 2.38 | 1.08 | 100 | 445 |
| KE1328 | 2.0 | 50 | 7.9 | 201 | 0.31 | 7.9 | 0.99 | 0.45 | 250 | 1112 |
| KE1338 | 2.7 | 69 | 10.2 | 259 | 0.31 | 7.9 | 1.32 | 0.60 | 250 | 1112 |
| KE1348 | 4.0 | 102 | 14.2 | 360 | 0.31 | 7.9 | 1.67 | 0.76 | 250 | 1112 |
| KE1358 | 6.0 | 152 | 20.4 | 520 | 0.31 | 7.9 | 2.23 | 1.04 | 250 | 1112 |
| KE1368 | 8.0 | 203 | 26.8 | 679 | 0.31 | 7.9 | 2.86 | 1.30 | 250 | 1112 |
| KE1378 | 10.0 | 254 | 33.0 | 838 | 0.31 | 7.9 | 3.52 | 1.60 | 250 | 1112 |
| KE1388 | 12.0 | 305 | 42.0 | 1067 | 0.31 | 7.9 | 4.62 | 2.10 | 250 | 1112 |



K502 Ball-Lok Tool with adjustable Tension and automatic cut off Weight .94Lbs (.43Kg)

316 Stainless Steel Package Quantity 100



Uncoated

| Cat. No. | Maximum Bundle Diameter | | Approximate Length | | Approximate Width | | Approximate Weight | | Min. Loop Tensile Strength | |
|----------|-------------------------|-----|--------------------|------|-------------------|-----|--------------------|------|----------------------------|------|
| | in | mm | in | mm | in | mm | Lbs. | Kg. | Lbs | N |
| KE0128 | 2.0 | 50 | 7.90 | 201 | 0.18 | 4.6 | 0.57 | 0.26 | 100 | 445 |
| KE0138 | 2.7 | 69 | 10.2 | 259 | 0.18 | 4.6 | 0.70 | 0.32 | 100 | 445 |
| KE0148 | 4.0 | 102 | 14.2 | 360 | 0.18 | 4.6 | 0.92 | 0.42 | 100 | 445 |
| KE0158 | 6.0 | 152 | 20.4 | 520 | 0.18 | 4.6 | 1.32 | 0.60 | 100 | 445 |
| KE0168 | 8.0 | 203 | 26.8 | 679 | 0.18 | 4.6 | 1.76 | 0.80 | 100 | 445 |
| KE0178 | 10.0 | 254 | 33.0 | 838 | 0.18 | 4.6 | 2.07 | 0.94 | 100 | 445 |
| KE0188 | 12.0 | 305 | 42.0 | 1067 | 0.18 | 4.6 | 2.38 | 1.08 | 100 | 445 |
| KE0328 | 2.0 | 50 | 7.90 | 201 | 0.31 | 7.9 | 0.99 | 0.45 | 250 | 1112 |
| KE0338 | 2.7 | 69 | 10.2 | 259 | 0.31 | 7.9 | 1.32 | 0.60 | 250 | 1112 |
| KE0348 | 4.0 | 102 | 14.2 | 360 | 0.31 | 7.9 | 1.67 | 0.76 | 250 | 1112 |
| KE0358 | 6.0 | 152 | 20.4 | 520 | 0.31 | 7.9 | 2.23 | 1.04 | 250 | 1112 |
| KE0368 | 8.0 | 203 | 26.8 | 679 | 0.31 | 7.9 | 2.86 | 1.30 | 250 | 1112 |
| KE0378 | 10.0 | 254 | 33.0 | 838 | 0.31 | 7.9 | 3.52 | 1.60 | 250 | 1112 |
| KE0388 | 12.0 | 305 | 42.0 | 1067 | 0.31 | 7.9 | 4.62 | 2.10 | 250 | 1112 |



KE922 Manual Tensioning Tool with tail cut-off lever Weight 1.25Lbs (.57Kg)

Custom Length Ball-Lok Banding System

Available in both 304 and 316 Stainless steel. 2 widths 0.18" (4.6mm) and .31" (7.9mm). Apply by hand or use the K502 or KE922 tools
For further details please contact sales desk

Bands and Heads

| Part No. | Width | Pack Type | Material |
|----------|-------|-------------|--------------|
| | Mm | | |
| CE1569 | 7.9 | 100m reel | 304 S. Steel |
| CE4569 | 7.9 | 100m reel | 316 S. Steel |
| CB1569 | 7.9 | Box of 1000 | 316 S. Steel |
| CE3569 | 4.6 | 100m reel | 304 S. Steel |
| CE2569 | 4.6 | 100m reel | 316 S. Steel |
| CB2569 | 4.6 | Box of 1000 | 316 S. Steel |



Heads: Box of 1000
CB1569, CB2569



Band: 100m per Reel
CE3569, CE2569
CE1569, CE4569