

# CABLE DRUM HANDLING

## CDR2 Cable Drum Rotators

Heavy Duty all steel welded fitted with one fixed and one adjustable diablo shaped steel roller with sealed bearings.  
Maximum drum payload 1500kgs.  
Finish: Painted  
Drum dia. max. 2400mm Drum dia. min, 300mm.  
Drum width Adustable.  
Size each 1000mm x 225mm x 120mm. Weight per pair 54Kgs.



## CDR3 Cable Drum Rotators

Rollers - Zinc plated steel - adjustable and fitted with sealed bearings.  
Maximum Drum payload 200Kgs.  
Finish: Zinc plated.  
Drum dia. max. 750mm Drum dia. min. 200mm  
Drum width 520mm  
Base size 630mm x 550mm Weight 16Kgs.



## DTS1 Drum Tip Stand

For ease of lifting and payout of cable.  
All steel welded tubular frame.  
Max. drum dia. 1750mm  
Max. drum width 930mm  
Drum weight 750Kgs.  
Paint finish.



## Cable Ramp

The Cable Ramp is designed to support and guide the cable directly from the cable drum and directly into the trench or duct mouth in a controlled manner, by means of a series of rollers. The unit is designed and built to order and therefore can be made to your specification.  
Paint finish.



## CDS1 Universal Cable Drum Stand

Lightweight unit suitable for a variety of cabling applications.  
Complete with spindle.  
Accommodates drums up to 600mm diameter and 500mm wide.  
Zinc plated frame.  
Max. drum weight 100kgs.

