

The Charles Endirect STAINLESS STEEL FEEDER PILLARS

The Charles Endirect range of brushed Stainless Steel Feeder Pillars are manufactured from 3mm Grade 304 stainless steel and are supplied complete with 12mm backboard and earth strap. These high quality pillars have a life expectancy of 50 years. Available in three styles, FMP/S and SMP/S Pillars give you a choice of either sealed or flush fitting doors, BDP/S Pillars are manufactured with hinged doors.

Charles Endirect Stainless Steel Feeder Pillars can be supplied empty or pre-wired; the BDP range will accept our Stainless Steel Distribution Boards.

SPECIFICATIONS

SMP/S PILLARS

Manufactured from 3mm Grade 304 stainless steel. Powder coat or paint finish available on request. Backboard – 12mm external grade plywood treated with water repellent. Detachable door with watertight seal. Earth stud fitted with an M6 brass earth bolt, nuts and washer on body and door. Ground level clearly marked. Integral Root – can be painted if required. Earth strap fitted. Tri-head locks.

FMP/S PILLARS

Manufactured from 3mm Grade 304 stainless steel. Powder coat or paint finish available on request. Backboard – 12mm external grade plywood treated with water repellent. Detachable flush fitting door – easy access. Earth stud fitted with an M6 brass earth bolt, nuts and washer on body and door. Ground level clearly marked. Integral Root – can be painted if required. Earth strap fitted. Tri-head locks.

BDP/S PILLARS

Manufactured from 3mm Grade 304 stainless steel. Powder coat or paint finish available on request. Backboard – 12mm external grade plywood treated with water repellent. Hinged door, water tight seal – stainless steel block hinges. Earth stud fitted with an M6 brass earth bolt, nuts and washer on body and door. Detachable painted root. Earth strap fitted. Tri-head locks. Anti-vandal locks available – CLL.



DIMENSIONS mm

REF	EXTERNAL			O/A	BACKBOARD		WORKING	
	HEIGHT	WIDTH	DEPTH		ROOT	HEIGHT		WIDTH
SMP/S								
SMP30/S	700	160	150	300	1000	600	150	130
SMP40/S	700	210	150	300	1000	600	200	130
FMP/S								
FMP30/S	700	160	150	300	1000	570	145	130
FMP40/S	700	210	150	300	1000	570	145	130
BDP/S								
BDP60/S	850	350	225	300	1150	750	330	205
BDP70/S	950	450	250	300	1250	850	430	230
BDP80/S	1050	550	275	300	1350	950	530	255
BDP90/S	1150	650	300	300	1450	1050	630	280

The facts and information offered in this document are given in good faith, and are correct at the time of going to press. Charles Endirect Ltd reserves the right to change products and specification without prior notification.

