

## DENSYL TAPE

**DESCRIPTION** A cold applied tape which remains plastic over a wide temperature range. It is non-hardening and non-cracking. It is highly resistant to mineral acids, alkalis, salts and micro-organisms and highly impermeable to water, water vapour and gases. For the protection of buried or exposed pipes, rods, cables, valves and metal fittings from corrosion. Waterproofing of cables and thermal insulation.

**COMPOSITION** Non-woven synthetic fibre fabric impregnated and coated with a neutral compound based on saturated petroleum hydrocarbons (petrolatum) and inert siliceous fillers. It is formulated particularly for use at tropical temperatures. The tape is supplied in rolls in a range of widths.

TYPICAL PROPERTIES	TEST METHOD	DATA
<b>Breaking Strength</b>	ASTM D1000	200 N/50mm minimum
<b>Elongation at Break</b>	ASTM D1000	10% average
<b>Breakdown Voltage (55% overlap)</b>		16kV minimum
<b>Resistance to Cathodic Disbonding</b>	ASTM G8 – 30 days	<500mm <sup>2</sup>
<b>Resistance to Acids, Alkalis and Salts</b>		Excellent
<b>Temperature Range</b> <i>For Application</i> <i>For Service</i>		5°C to 55°C -20°C to 70°C
<b>Roll Length</b>		10 metres minimum
<b>Thickness</b>	ASTM D1000	1.15mm average
<b>Weight</b>		1.44 kg/m <sup>2</sup> average

<b>RECOMMENDED PRIMER</b>	Denso Paste, Denso Priming Solution
---------------------------	-------------------------------------

### Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS  
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS  
FURSE EARTHING  
www.cablejoints.co.uk  
**Thorne and Derrick UK**

Tel 0044 191 490 1547 Fax 0044 191 477 5371  
Tel 0044 117 977 4647 Fax 0044 117 9775582