



## Static earth lead and plier clamp

Description	Cable length (max)	Weight each	Part No.
Static earth lead and plier clamp	3 metres	0.56kg	<b>SK010</b>

Clamp certification II 1GD T6 Approved

A multicored high-tensile steel cable with a medium duty hard anodized diecast aluminium clamp. The Cen-Stat™ cable has an orange Hytrel coating and is pre-terminated with an M10 compression ring terminal. The clamp has stainless steel contact teeth.



## Static earth lead and heavy duty clamp

Description	Cable length (max)	Weight each	Part No.
Static earth lead and heavy duty clamp	5 metres	1.09kg	<b>SK020</b>

Clamp certification II 1GD T6

A multicored high-tensile steel cable with a heavy duty passivated carbon steel clamp. The Cen-Stat™ cable has an orange Hytrel coating and is pre-terminated with an M10 compression ring terminal. The clamp has twin tungsten carbide contact teeth.



## Static discharge reel and plier clamp

Description	Cable length (max)	Weight each	Part No.
Static discharge reel and plier clamp	6.1 metres	4kg	<b>SK030</b>

Clamp certification II 1GD T6. Reel certification II 2GD T6

A multicored galvanised steel cable with a medium duty hard anodized diecast aluminium clamp. The cable is housed in a self-retracting cable drum with an instant lock mechanism. The clamp has stainless steel contact teeth.



## Static discharge reel and heavy duty clamp

Description	Cable length (max)	Weight each	Part No.
Static discharge reel and heavy duty clamp	15.2 metres	5.9kg	<b>SK040</b>

Clamp certification II 1GD T6. Reel certification II 2GD T6

A multicored galvanised steel cable with a heavy duty passivated carbon steel clamp. The cable is housed in a self-retracting cable drum with an instant lock mechanism. The clamp has twin tungsten carbide contact teeth.