

Low Voltage Heatshrink Joint Kits

Straight Joints for Paper Cables & Transitions to Polymeric Cables



Designed for jointing paper insulated cables and transitions from paper to polymeric cables up to 1kV.

Kits are available to cater for all cable types likely to be encountered up to a maximum of 300mm² including unarmoured cables designs.

Kits contain full installation instructions, necessary re-insulation sleeves and outer heavy walled protection tube to re-build cable sheath. Where appropriate earth bonding components and a steel cage or mesh is supplied to restore the cables armour.

Henley's low voltage heatshrinkable joint kits general comply with BS7888 Part 2 1998.

- 4 core joint designs available.
- Size range from 16.0 to 300.0mm².
- Can be designed to cater for both armoured or unarmoured applications.



A subsidiary of TT electronics plc



Our name carries power... Everywhere

Kit Reference for 4 core Paper Straight Joint	Kit Reference for 4 core Transition Straight Joint	Conductor Size Range (mm ²).
LVJPA-4-1625	LVJTR-4-1625	16.0 – 25.0
LVJPA-4-3550	LVJTR-4-3550	35.0 – 50.0
LVJPA-4-70150	LVJTR-4-70150	70.0 – 150.0
LVJPA-4-185300	LVJTR-4-185300	185.0 – 300.0

For unarmoured applications add suffix "U" when ordering i.e. LVJTR-4-1625U



WT Henley Ltd can configure LVJPO, LVJPA and LVJTR kits to suit specific customer requirements which can include necessary connectors. Please contact Henley's Sales Department.



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
 TEL 0044 191 490 1547 FAX 0044 477 5371
 TEL 0044 117 977 4647 FAX 0044 977 5582
 WWW.THORNEANDDERRICK.CO.UK



A subsidiary of TT electronics plc



General Note The equipment detailed in this publication should be installed by a suitably qualified person. WT Henley Limited reserves the right to make changes in product specification without notice or liability. All information is subject to WT Henley's own data and is considered accurate at time of going to print.

© 2003 WT Henley Limited. All rights reserved. No part of this document may be copied or reproduced in whole or in part without prior written approval of WT Henley Limited.