



Gear House, Saltmeadows
Road
Gateshead, Tyne & Wear NE8
3AH
Tel: (0191) 490 1547
Fax: (0191) 477 5371

Low Voltage Zero Halogen Cable Joints For limited Fire Hazard Cables



- Fire tested and compliant with London underground standards 2-0100-002 or the fire safety of materials and E4156 for the cable standard
- Slim profile and unlimited shelf life Complete with range taking mechanical shearbolt connectors
- Full range of joints available for all cable types including power and multicore cables

Shrink Polymer Systems can now offer a range of heatshrink joints suitable for both single and multicore low smoke fume zero halogen cables.

Developed for London Underground for use within the tunnels and above surface, the system incorporates flame retardant, non halogen polyolefin heatshrink tubing with a meltable inner liner that itself has excellent flame retardant properties with reduced acid gas emission and smoke generation.



The system incorporates a flexible outer fire barrier tube that provides a high degree of fire resistance. For installations outside of the tunnels this can be omitted.

For ease of use, the range comes complete with range finding mechanical shearbolt connectors. Slim in profile the joints can be installed in horizontal and vertical planes and have an unlimited shelf life.

| HEATSHRINK JOINTS TO SUIT 1-4 CORE XLPE/SWALSOH | | |
|--|--------------------------|----------------|
| PART NUMBER | CABLE RANGE | VOLTAGE |
| SPA NHF 1.5-2.5- | 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 4-6- | 4 - 6mm ² | 600/1000V |
| SPA NHF 10-16- | 10 - 16mm ² | 600/1000V |
| SPA NHF 25-50- | 25 - 50mm ² | 600/1000V |
| SPA NHF 70-95- | 70 - 95mm ² | 600/1000V |
| SPA NHF 120-185- | 120 - 185mm ² | 600/1000V |
| SPA NHF 240-300- | 240 - 300mm ² | 600/1000V |
| SPA NHF 400-630- | 400-630mm ² | 600/1000V |
| SPA NHF 800-1000- | 800-1000mm ² | 600/1000V |

Notes:-

- 1 For non armoured joints, omit letter (A) from the part number
- 2 Add last digit to part number to indicate number of cores



Gear House, Saltmeadows
Road
Gateshead, Tyne & Wear NE8
3AH
Tel: (0191) 490 1547
Fax: (0191) 477 5371

HEATSHRINK JOINTS TO SUIT MULTICORE XLPE/SWALSOH

| PART NUMBER | CABLE RANGE | VOLTAGE |
|--------------------|----------------------------------|-----------|
| SPA NHF 1.5-2.5-5 | 5 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-7 | 7 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-12 | 12 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-19 | 19 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-27 | 27 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-37 | 37 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-48 | 48 core 1.5 - 2.5mm ² | 600/1000V |
| SPA NHF 1.5-2.5-61 | 61 core 1.5 - 2.5mm ² | 600/1000V |

Notes:-

- 1 For non armoured joints, omit letter (A) from the part number
- 2 Add last digit to part number to indicate number of cores

Low Voltage Zero Halogen Cable Joints For Fire Resistant Cables



- Designed for use where low smoke fume or fire resistance is essential
- Designed to meet the general requirements of IEC 331 and VDE 0472 for fire resistance and test method ASTM D-350 method B for flammability
- Joints available for all types of LV and MV cables

Fire resistant cables are usually installed where vital electrical circuits are required to continue operating in the event of a fire. Shrink Polymer Systems can provide joint kits to suit these cable types for both single and multicore configurations.

In addition to utilising LSF/Zero halogen heatshrink tubes and fire barrier tubes, the joints incorporate mica tape over each of the cores.

Mica tape is a slit silica tape constructed from 96% pure SiO₂ silica fiber, coated one side with a pressure sensitive adhesive backing that facilitates installation. The adhesive decomposes at high temperatures, leaving a perfectly taped core

Suitable for use at 1800°F (982°C), and able to withstand short term exposure up to 3000°F (1650°C), mica tape when combined with our proven zero halogen joint range, enables the joint to work in these extreme conditions.

Contact us for more details.

