

# Legend Thermal Heatshrink Labeling Solution

Silver Fox has taken a fresh look at the requirements of process industries and developed a new, patented thermal heatshrink solution.

There are 3 sizes of heatshrink available, all with 3:1 shrink ratio. Labels can be produced in conjunction with the following Silver Fox softwares:

- Labacus Innovator E&I Advanced
- Labacus Innovator Global Advanced
- Labacus Innovator Professional

All of these softwares incorporate our unique time saving Plug'N'Play printer driver, enabling the user (when working with our software) to simply to plug in the printer and print - first time every time, for any application Windows 95 or higher.

Silver Fox use only the best quality heatshrink materials; you can choose between our 'Standard' or 'LHSH' (zero-halogen) grade thermal solutions – we would be delighted to advise as to which is best suited to your application.

#### Key Benefits

- ✓ 3 sizes available to cover your entire labeling needs (all 3:1 shrink ratio)
- ✓ Produce labels in lengths of 10mm to 50mm from one continuous roll
- ✓ For use with heat guns
- ✓ Low shrink-down temperature
- ✓ Run up to 6 rolls at the same time
- ✓ Use with our Labacus Innovator range of labeling softwares incorporating our unique Plug'N'Play interface



SILVER FOX  
Make Labeling your Signature for Quality and Reliability



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS  
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS  
FURSE EARTHING  
www.cablejoints.co.uk  
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371  
Tel 0044 117 977 4647 Fax 0044 117 9775582

# Legend Thermal Heatshrink Labeling Solution

<b>Material</b>	Polyolefin
<b>Shrink Ratio</b>	3:1
<b>Operating Temperature</b>	-55°C to +135°C
<b>Min. Shrink Temperature</b>	90°C
<b>Dialectic Strength</b>	37kV/mm
<b>Specifications</b>	UL224 125°C 600VV-1, CSA C22.2 No.198.1
<b>Testing</b>	MIL-STD-202G (Method 106G) <i>Moisture Resistance</i>  MIL-STD-202G (Method 108A) <i>Elevated Ambient Temperature – 1000 hrs @ 85°C</i>  MIL-STD-810F (Method 502.4) <i>Storage (Low Temperature) -40°C</i>  IEC60068-2-52 <i>Test kb Salt Mist (Cyclic)</i>  H <sub>2</sub> S (Hydrogen Sulphide) Sour Ageing

TECHNICAL  
DATA

Product Code	Inside Cable Dia. Expanded	Outside Cable Dia. Recovered	Roll Length	Colors Available
LHS6-2(22)TY	6mm	2mm	22 metres	Yellow
LHS6-2(22)TW	6mm	2mm	22 metres	White
LHS12-4(6)TY	12mm	4mm	6 metres	Yellow
LHS12-4(6)TW	12mm	4mm	6 metres	White
LHS12-4(18)TY	12mm	4mm	18 metres	Yellow
LHS12-4(18)TW	12mm	4mm	18 metres	White

ORDER  
CODES

## Accessories

Product Code	Description
HSAG-1	Hot Air Gun
LHIG-S	Legend Heat Shrink Internal Printer Guide Set
LHIS-1	Legend Heat Shrink Internal Guide (3/1)
LHIS-2	Legend Heat Shrink Internal Guide (6/2)
LHIS-3	Legend Heat Shrink Internal Guide (12/4)

Information contained in this product data sheet is based on data we believe to be reliable. The typical values listed are not for use in specifications. They are given for information only and without guarantee and do not constitute a warranty. The purchaser should independently determine prior to use the suitability of this product for their specific purpose.



10050165



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS, FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS  
11KV-33KV CABLE JOINTS & CABLE TERMINATIONS  
FURSE EARTHING  
www.cablepoints.co.uk  
Thorne and Derrick UK  
Tel: 0044 191 426 1547 Fax: 0044 191 477 5311  
Tel: 0044 117 977 4647 Fax: 0044 117 977 5582