

PANDUIT® Cord and Receptacle Lockouts

Global Plug Lockout



- Compact, universal design accommodates most 220-240 volt plugs
- Quickly and easily installed
- Nylon construction offers great strength and durability
- Accepts Panduit PSL-3, PSL-4, PSL-5 and PSL-11 series locks (see [pages 13-14](#))
- Requires lock with shackle diameter between 0.20" (6 mm) and 0.37" (9 mm)
- Note: cannot be used with North American 120 VAC plugs

Part Number	Description	Std. Pkg.*
PSL-PI	Global Plug Lockout	1

Prevents a plug from being plugged in.

Cord Lockouts



- Two sizes to accommodate small and large plugs
- Locks must have 0.38" (10 mm) or smaller shackle diameter

Part Number	Description	Inside Dimension In. (mm)	Std. Pkg.*
PSL-CL110	Lockout for 120 Volt AC Cord	2.00 x 2.00 x 3.50 (51 x 51 x 89)	1
PSL-CL480	Lockout for 240-480 Volt AC Cord	3.25 x 3.25 x 6.5 (83 x 83 x 165)	1

Prevents a plug from being plugged in.

Receptacle Blockout



- Prevent overloading the circuit, which may cause damage to equipment plugged into the other receptacle
- Prevent use of the open receptacle for devices which may induce electrical interference in computer equipment, causing data transmission problems or damage of computer controlled equipment

Part Number	Description	Std. Pkg.*
PSL-ERB	Blockout for open electrical receptacles	1

Used to prevent use of an open electrical receptacle.



Place PSL-ERB blockout device over outlet so that the hole pattern in the blockout lines up with the 3 holes in the receptacle to be used.



Insert plug into the receptacle. The blockout is now held firmly in place by the plug and the second receptacle is blocked out.