

HDCO Heavy Duty Cut-out

MC300

Features

- ACCEPTS BS 88 J TYPE FUSE LINKS
- MAXIMUM RATING 300A
- FUSE CARRIER WITH 83MM CENTRES
- MOULDED IN WHITE GLASS FILLED POLYESTER THERMOSET MATERIAL
- ALL CONTACTS MANUFACTURED FROM SOLID BRASS SECTION WITH 2 TERMINAL PINCHING SCREWS PER CONDUCTOR
- CABLE ENTRY AND EXITS THROUGH PVC GROMMET
- MAXIMUM CABLE SIZE 185MM²
- OPTIONAL "NEUTRAL" LINK
- REFER TO PAGE 14 FOR FUSE BASES, CONTACTS AND FUSE HANDLES



Type 1 Clamp fitting for 35mm² to 120mm²



Type 2 Clamp fitting for 185mm²



Type 3 Tunnel Terminal for 95mm²



Ref.	Description	Max Fuse rating	Max cable size	Dimensions in mm
MC300	Single Phase Heavy Duty Cut-out with fuse	300A	185mm ²	H162 W135 D76

Ref.	Description	Max Fuse rating	Max cable size	Dimensions in mm
MC300N	Single Phase Heavy Duty Cut-out with neutral link	300A	185mm ²	H162 W135 D76

Ref.	Fittings for MC300
A	Type 2 contact Fittings 185mm ² / 185mm ²
B	Type 2/3 contact Fittings 185mm ² / 2 x 95mm ²
C	Type 3 contact Fittings 2 x 95mm ² / 2 x 95mm ²
H	Type 1 contact Fittings 35-120mm ² / 35-120mm ²
J	Type 1/3 contact Fittings 35-120mm ² / 2 x 95mm ²

Ref.	Fittings for MC300N
N/A	Type 2 contact Fittings 185mm ² / 185mm ²
N/B	Type 2/3 contact Fittings 185mm ² / 2 x 95mm ²
N/C	Type 3 contact Fittings 2 x 95mm ² / 2 x 95mm ²
N/E	Type 1 contact Fittings 35-120mm ² / 35-120mm ²
N/F	Type 1/3 contact Fittings 35-120mm ² / 2 x 95mm ²

CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS

FURSE EARTHING

www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371

Tel 0044 117 977 4647 Fax 0044 117 9775582