

Features

ACCEPTS BS 88 J TYPE FUSE LINKS

MAXIMUM RATING 300A

FUSE CARRIER WITH 83MM CENTRES

MOULDED IN WHITE GLASS FILLED POLYESTER THERMOSET MATERIAL

ALL CONTACTS MANUFACTURED FROM SOLID BRASS
SECTION WITH 2 TERMINAL PINCHING SCREWS
PER CONDUCTOR

CABLE ENTRY AND EXITS THROUGH PVC GROMMET

MAXIMUM CABLE SIZE 185MM²

OPTIONAL "NEUTRAL" LINK

REFER TO PAGE 14 FOR FUSE BASES, CONTACTS AND FUSE HANDLES





Type 1 Clamp fitting for 35mm² to 120mm²



Type 2 Clamp fitting



Type 3 Tunnel Terminal for 95mm²

MC300N N/B

| Ref. | Description | Max Fuse rating | Max cable size | Dimensions in mm |
|--------|---|-----------------|--------------------|------------------|
| MC300 | Single Phase Heavy Duty Cut-out with fuse | 300A | 185mm ² | H162 W135 D76 |
| | | | | |
| Ref. | Description | Max Fuse rating | Max cable size | Dimensions in mm |
| MC300N | Single Phase Heavy Duty Cut-out with neutral link | 300A | 185mm ² | H162 W135 D76 |

| Ref. | Fittings for MC300 | |
|------|--------------------|--|
| Α | Type 2 contact | Fittings 185mm²/ 185mm² |
| В | Type 2/3 contact | Fittings 185mm²/ 2 x 95mm² |
| С | Type 3 contact | Fittings 2 x 95mm ² / 2 x 95mm ² |
| Н | Type 1 contact | Fittings 35-120mm ² / 35-120mm ² |
| J | Type 1/3 contact | Fittings 35-120mm ² / 2 x 95mm ² |

| Ref. | Fittings for MC300N | |
|------|---------------------|--|
| N/A | Type 2 contact | Fittings 185mm²/ 185mm² |
| N/B | Type 2/3 contact | Fittings 185mm ² / 2 x 95mm ² |
| N/C | Type 3 contact | Fittings 2 x 95mm ² / 2 x 95mm ² |
| N/E | Type 1 contact | Fittings 35-120mm ² / 35-120mm ² |
| N/F | Type 1/3 contact | Fittings 35-120mm ² / 2 x 95mm ² |





CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS