

TECHNICAL DATASHEET – R26

Electric Point Heater



Specification RT/E/S/40045
Voltage Rating 0.3/0.5 kV
Description Flexible tinned copper conductors,
EPR insulation, cores laid up, PCP sheath

No. of cores & Nominal Cross Sectional Area of Conductor	No. & Nominal Diameter of Strands	Maximum DC Conductor Resistance @ 20°C	Nominal Overall Diameter	Nominal Weight
no x mm ²	no/mm	Ω/Km	mm	Kg/Km
4 x 1.50	30/0.25	13.70	13.90	267.00
4 x 2.50	50/0.25	8.21	16.10	374.00
4 x 4.00	56/0.30	5.09	18.10	494.00
8 x 1.50	30/0.25	13.70	18.30	439.00
8 x 2.50	50/0.25	8.21	21.20	627.00
8 x 4.00	56/0.30	5.09	23.10	773.00
8 x 6.00	84/0.30	3.39	24.70	956.00

General Note

AEI Cables reserves the right to amend the product information without notice or liability.
The information is considered accurate at the time of going to print.



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK