



## Type UL-X



Part of our UL Range  
 2006 Catalogue Page 4.5.0

UL-X Type Explosion-proof glands provide a compound seal preventing the passage of gas or vapours through the gland and the propagation of flame into the cable core. The glands are UL listed; suitable for Marine Shipboard non-armoured cable; NEMA 4X applications and are Deluge-Proof.

DESIGN STANDARD	UL2225 & UL514B		
CERTIFICATION	CLASS I, DIVISION 2 GAS GROUPS ABCD		
CERTIFICATE	File No. E248936		
GLAND MARKING	Example: UL-XB 20 1/2 NPT PEPPERS GU15 3BT UK CL I DIV 1 ABCD -25+85°C 4X		
LISTED APPLICATION	Class I, Division 2 ABCD UL-X type glands will maintain the Explosion-Proof integrity of electrical equipment when used with suitable listed cable types. <b>NEC 505:</b> Class I, Zone 2, Gas Groups IIC, IIB, IIA. UL-X type glands will maintain the Flameproof integrity of electrical equipment when used with suitable listed cable types.		
INGRESS PROTECTION	NEMA 4X. Meets the requirements of DTS01 1991		
CURING TIME	@21°C Conductor termination can be effected after 1 hour The equipment can be energised after 4 hours		
MATERIALS	Brass CZ121 (UL-XB) Stainless Steel 316 (UL-XS) Inner LSOH compound		
OPTIONS	THREADS	ISO Metric; NPT; NPSM	
	PLATING	Zinc (ZP); Nickel (NP); Tin (TP); Electroless Nickel (EN) - All entry threads are nickel plated as standard	
OPERATING TEMPERATURES	-25°C to +85°C		

<b>ACCESSORIES</b>	Locknut - Brass (ACBLN); 316 Stainless Steel (ACSLN) Earth Tag - Brass (ACBET), 316 Stainless Steel (ACSET) IP Washer - Nylon (ACNSW); Red Fibre (ACFSW) Serrated Lock Washer - 316 Stainless Steel (ACSSW), Galvanised Steel (ACGSW) Shroud - PVC (ACSPVC)
--------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>EXAMPLE PART NUMBER</b>	Sample: <b>UL-XB / 20 / 050NPT</b>  UL-X - Gland type UL-*B - Material (Brass) 20 - Fitting size = 20 050NPT - ½" NPT entry thread
----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------

Gland Size	Trade Size		Entry Thread Length	Max Across Corners	Max Protrusion Length	Maximum Sheath Diameter [C]	Shroud Size
	Metric	NPT	[B] NPT	[A]			
20s	M20	½" or ¾"	0.783	1.102	1.654	0.461	L24
20	M20	½" or ¾"	0.783	1.299	1.732	0.551	L30
25	M25	¾" or 1"	0.795	1.630	1.890	0.787	L38
32	M32	1" or 1¼"	0.985	1.992	2.087	1.035	L46
40	M40	1¼" or 1½"	1.008	2.382	2.126	1.268	L55
50	M50	2"	1.059	2.815	2.126	1.736	L65
63	M63	2½"	1.571	3.465	2.165	2.205	L80
75	M75	3"	1.634	4.134	2.362	2.677	L90

All Dimensions are in inches

**NOTES:**

- Gland Size does not necessarily equate to the entry thread size
- Integral entry thread seal option is not available for glands with tapered entry threads. IP washers can be supplied if required
- Please note that dimensions (A) and (B) may differ for glands with parallel entry threads. Please refer to our thread data tables for specific dimensions
- Unless otherwise stated ISO Metric entry threads have a 1.5mm pitch
- Full assembly instructions are supplied with glands, the instructions must be read prior to installation and adhered to in full
- For Class I Group A locations, the joint made by fitting the gland to the enclosure female thread must comply with standard UL 886 clause 6.4.1 as follows:-
  - NPT threads must have at least five threads fully engaged
  - Metric and NPS threads must have at least eight threads fully engaged

