

# WS 40

## Motorized Semi-con URD Shield Removal




- For removal of "bonded" semi-con shield on 5 to 34.5 KV cables
- .625 to 1.875 in (15.88 to 47.63 mm) cable O.D.
- For shaving semi-con shields off XLPE, polyethylene and EPR
- Master shaving bushings and adapter sleeves are sold separately
- Available in 115 VAC
- Made in the U.S.A.
- Length: with master bushing – 12 in (305 mm)
- Weight: WS 40 – 13 lb (5.90 Kg); Master shaving bushing – 1 lb (454 g); Adapter sleeve – 4 oz (113.5 g)
- WS 40 115 VAC Part No.: 17900

### Ordering Information

1. Select the master shaving bushing below
2. Select the adapter sleeves
3. **Cable sample is preferred**

Master Shaving Bushing	O.D. Over Semi-Con		Replacement Blade
	(inch)	(mm)	
MSBA	.600 - .885	15.24 - 22.48	CB 43 (Part No.: 17918)
MSBB	.840 - 1.140	21.34 - 28.96	CB 43 (Part No.: 17918)
MSBC	1.095 - 1.380	27.81 - 35.05	CB 43 (Part No.: 17918)
MSBD	1.335 - 1.485	33.91 - 37.72	CB 43 (Part No.: 17918)
MSBD-1	1.495 - 1.635	37.97 - 41.53	CB 43-1 (Part No.: 17951)
MSBE	1.560 - 1.650	39.62 - 41.91	CB 43-1 (Part No.: 17951)
MSBE-1	1.660 - 1.905	42.16 - 48.39	CB 43-2 (Part No.: 17952)



### ADAPTER SLEEVES:

Select an adapter sleeve having the size nearest the OD of your cable semi-con. Then select a sleeve one size larger and a sleeve one size smaller. Usually three sleeves will handle cable variation.