



WS 9D, WS 9E

Transmission Semi-con Shaving Tools

- For shaving bonded semi-con from transmission voltage cables
- Radius or taper cut of semi-con shield
- Shaves in a helical, spiral pattern
- Aluminum Oxide Kit (TK 1) can be used for additional smoothing
- Made in the U.S.A.
- Length: 16.2 in (411 mm)
- Weight: 2.74 lb (1244 g)
- WS 9D Part No.: 38035
- WS 9E Part No.: 28215-3



WS 9D

Model	Cable O.D. Range (inch)	Cable O.D. Range (mm)	Style of Cut	Replacement Blade
WS9D	1.90 to 3.625	48.3 to 92.1	Radius Cut	CB 40X (Part No.: 21715)
WS9E	1.90 to 3.625	48.3 to 92.1	Taper Cut	CB 98 (Part No.: 28201)

WS 9S SERIES

Semi-con Shaving Tools

- For shaving bonded semi-con cables
- Radius or taper cut of semi-con shield
- Shaves in a helical, spiral pattern
- Aluminum Oxide Kit (TK 1) can be used for additional smoothing
- Made in the U.S.A.
- Length: 8 in (200 mm)
- Weight: 1.9 lb (860 g)
- WS 9S Part No.: 38430
- WS 9S-T Part No.: 38435



WS 9S

Model	Cable O.D. Range (inch)	Cable O.D. Range (mm)	Style of Cut	Replacement Blade
WS9S	0.50 to 2.50	12.7 to 63.5	Radius Cut	CB 40X (Part No.: 21715)
WS9S-T	1.80 to 2.50	45.7 to 63.5	Taper Cut	CB 98 (Part No.: 28201)

SECONDARY DIST.

PRIMARY DIST. (OH)

PRIMARY DIST. (URD)

SPECIALTY DIST.

TRANSMISSION