

Item Code: **SM551**

Item Description: **Fine Ribbed Rubber Matting to 11,000v**

SM551 Fine Ribbed Rubber Matting to 11,000v is a high quality matting with the regulation standard, stamped on the reverse of the roll at 1000mm intervals. Fully certified and tested to 11,000 volts with a recommended safety working voltage of 450v. It has a fine ribbed, anti-slip surface pattern on one side and a cloth impression finish on the reverse.

- Fully tested to specification
- Health & Safety regulation material
- Fully traceable supply
- Regulatory branding on reverse every 1000mm
- Ensures safety for operatives at lower voltage switchboard and high equipment areas
- Anti-slip finish
- Low maintenance

Cut lengths available to order. **SM551** can also be supplied to order in colours and flame retardant, low smoke emission grades


Technical Information

Application	Electrical Safety, Health & Safety
Product	Anti Slip, Electrical Safety, Safety Matting
Thickness	6mm
Resistance to	Please Call
Colour	Black
Insert Req	No
Solid	Yes
Drainage Holes	No

Item Code: SM551

Other sizes and colours to special order.
Cut lengths to order.

All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for the intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.



Stock Roll Sizes	Weight	Specifications	Values
[m x m x mm]	[kg/M2]	[compound]	[typical]
10m x 0.91m x 6mm	6.80	Colour:	Black
10m x 1.0m x 6mm	6.80	Compound:	SBR/NR
10m x 1.2m x 6mm	6.80	Hardness [shore A]:	65°
		Density[SG]:	1.3
		Tensile Strength:	5 MPA
		Elongation[min]:	250%
		Abrasion Resistance:	180 mm ³
		Minimum Temperture	-20°C
		Maximum Temperture	+70°C