



**MD555 Electrosafe 40kv ASTM D178 /ANSI JS.7 Type 2 Class 3  
Electrical Rubber matting.**

Electrical switchboard Rubber matting fully tested to the above standards, to include full testing over the entire mat surface and stamped on the reverse every 100cm with identification coding.

An extremely Ultra High specification and High quality natural Rubber compound safety matting product able to withstand the following:

Dielectric test to 40,000v  
Surface proof test to 30,000v  
Working voltage 26,000v

Colour: Black  
Hardness: 60 shore A  
Density [SG]: 1.3  
Tensile Strength: 5.0 Mpa  
Elongation: 250%  
Temperature Range: -20/+70 deg c  
Abrasion Resistance: 200 mm3

Thickness [mm]	Roll size 10m x 0.91m	Roll size 22.5m x 1.2m	Weight/M2 [kgs-appx]
9.5	Ex Stock	Order	9.5

MD555 electrical switchboard matting performance

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Colour Fastness  
To sunlight, general cleaning and remedial treatment

Cleaning and Maintenance

Daily:	Vacuum clean. An upright unit with a powered cylindrical brush is ideal.
--------	--