

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS FURSE EARTHING www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371 Tel 0044 117 977 4647 Fax 0044 117 9775582



MD580 Electro Safe 50 kv VDE0303 Tested Fine ribbed Rubber electrical matting.

Fully tested in accordance with VDE0303 standard and stamped on the reverse every 100cm. High quality Rubber electrical safety matting made to exacting standards and fully certified and tested to 50,000v.

Working volt test 1000v

Colour: Grey

Hardness: 65 shore A

Density [SG]: 1.3

Tensile Strength: 5.0 Mpa Elongation: 250%

Temperature Range: -20/+70 deg c Abrasion Resistance: 180 mm3

Thickness	Roll size	Roll size	Weight/M2
[mm]	10m x 1m	10m x 1.2m	[kgs-appx]
4.5	Ex Stock	Ex Stock	5.5

MD580 Electrical safety matting performance

- Fully branded on reverse
- Extremely safe from electrical shock and hard wearing
- Positive safe grip from the flutes

Colour Fastness

To sunlight, general cleaning and remedial treatment

Cleaning and Maintenance

Daily:	Vacuum clean.	An upright unit with a powered cylindrical brush
	is ideal.	