


Similar to our Ty-Rap® range of flame retardant ties, these all-plastic ties are made from low smoke flame retardant Polyamide 6.6 and meet the requirements of UL 94 V-0. Ideal for use where low flammability and low smoke are necessary such as public transport / buildings, tunnels etc.



Technical Information

| | |
|---------------------|--|
| Material | Polyamide 6.6 |
| Temperature range | -40°C to +85°C |
| Colour | Milky white |
| Flammability rating | UL 94 V-0 |
| Other properties | Limited fire hazard (low smoke) Halogen free, Silicone free |

Ordering Information

| PRODUCT REF. | LENGTH L [mm] | WIDTH W [mm] | BUNDLE DIAMETER FROM ... TO [mm] | MINIMUM TENSILE STRENGTH [N] | QUANTITY [pieces] | TOOLING |
|--------------|---------------------|--------------------|--|------------------------------------|----------------------|--------------------------|
| TS1025HF | 100 | 2.5 | 2 - 24 | 90 | 100 | |
| TS1435HF | 140 | 3.5 | 2.5 - 36 | 180 | 100 | ERG299 |
| TS2045HF | 200 | 4.5 | 3 - 51 | 220 | 100 | TR227 |
| TS2845HF | 280 | 4.5 | 5 - 76 | 220 | 100 | WT193A |
| TS3645HF | 360 | 4.5 | 5 - 101 | 220 | 100 | |
| TS3675HF | 360 | 7.5 | 5 - 101 | 540 | 100 | ERG297, L-500-EU WT3D |

For tooling specifications see pages 104 to 111