




Pillar References	FP540	FP545	FP550	FP555	FP565
Height	1300	1650	1650	1650	1650
Width	1200	1500	1800	2050	2500
Depth	450	450	450	450	450
Internal Working Depth	415	415	415	415	415
Root	400	400	400	400	400
Backboard Height	1000	1220	1220	1220	1220
Backboard Width	1160	1480	1780	2000	2440
Weight (Kgs)	317	450	470	640	716
Roof Ventilation	Yes	Yes	Yes	Yes	Yes

(Dimensions in mm)

Specifications

- ◆ Fabricated from 5mm mild steel sheet.
- ◆ Standard finish is hot dipped galvanised to BS EN 1461.
- ◆ 18mm thick exterior grade ply backboard, treated with a clear water repellent.
- ◆ Pillar doors hinged using internal, heavy duty, hot-dipped galvanized hinges.
- ◆ Earth lug fitted to both pillar and door.
- ◆ Fitted with HD-1 stainless steel locks c/w covers and security bungs.
- ◆ Designed with a fully detachable root.
- ◆ Lifting lugs fitted.
- ◆ Pillars are of a welded construction.
- ◆ A4 document holder fitted to inside of door.
- ◆ Supplied with padlock facility.

Optional Extras

- ◆ Can be manufactured from stainless steel.
- ◆ Can be supplied painted leatherette black, grey or other colours on request.
- ◆ Pillar can be supplied for surface mounting.
- ◆ Can be supplied with a bitumen coated root.
- ◆ Other locks available on request.
- ◆ Door stay mechanism.
- ◆ Anti-graffiti / fly poster textured finish.
- ◆ Vandal resistant padlock bar (VRB).
- ◆ Other sizes available on request.
- ◆ Cut-outs and Isolators pre-fitted to your specifications.
- ◆ All pillars can be pre-wired.

Order Reference



Ref.	Pillar Size (mm)	Ref.	Material Type	Ref.	VRB Option	Ref.	Material Thickness
540	H=1300 W=1200 D=450	HDG	Hot Dip Galvanised	V	Vandal Resistant Padlock Bar (VRB)	5	5mm Thick
545	H=1650 W=1500 D=450	HDP	Hot Dip Galvanised and Painted (Grey as standard)	N	No VRB		
550	H=1650 W=1800 D=450						
555	H=1650 W=2050 D=450						
565	H=1650 W=2500 D=450						