

TECHNICAL DATASHEET – R25

Track Feeder



Specification RT/E/S/21101
Voltage Rating 0.65/0.75 kV
Description Stranded tinned copper conductors,
CSP sheath

No. of cores & Nominal Cross Sectional Area of Conductor	No. & Nominal Diameter of Strands	Conductor Material	Maximum DC Conductor Resistance @ 20°C	Nominal Overall Diameter	Nominal Weight
no x mm ²	no/mm		Ω/Km	mm	Kg/Km
1 x 150.00	37/2.25	Aluminium	0.206	20.50	581.00
1 x 161.00	91/1.53	Copper	0.109	25.90	2050.00
1 x 240.00	61/2.25	Aluminium	0.1250	29.60	1177.00
1 x 500.00	61/3.20	Aluminium	0.0605	42.00	2361.00
1 x 500.00	91/2.65	Copper	0.0369	42.30	5582.00
1 x 630.00	127/2.52	Copper	0.0286	45.90	6879.00
1 x 800.00	127/2.85	Aluminium	0.0367	50.20	3498.00
1 x 1000.00	127/3.20	Aluminium	0.0291	55.00	4226.00

General Note

AEI Cables reserves the right to amend the product information without notice or liability.
The information is considered accurate at the time of going to print.



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK