

3M QS2000B Cold Shrink Three Core Branch Joint 92-BV6210-1/C with Mechanical Connectors

Application

3M™ QS2000B 92-BV6210-1/C Cold Shrink Joints are designed for Branch splicing up to 12kV Umax voltage class, Three core polymeric power cable systems with copper tape screen & armour according to HD 620 (IEC 60502).

Kit Content

3M™ 92-BV6210-1/C Branch Joint includes the Cold Shrink QS2000B silicone splice body with integrated stress control device, conductive electrode, silicone elastomeric insulation and outer semi-conductive layer. Also included are Copper Screen sleeve, Constant Force springs for metallic screen and armour connection, mould shell, & mechanical connector.



Product Features

- The versatile design of the prefabricated one-piece cold shrink splice body allows installation on a wide range of cable sizes and types and a fast and easy installation at temperatures ranging from - 20°C to + 50°C.
- No heat or flame is needed during splice body installation.
- Mechanical connector provides quick and easy connection, with no special tooling.
- Solderless earth connection by means of Copper Stocking and Constant Force springs.
- No special tools are needed during splice installation.
- Scotchcast resin packs provide options to install in zones 1 & 2 hazardous areas as well as standard buried applications.

Installation

3M™ Cold Shrink technology ensures quick, easy and safe installation of the QS2000B Splice Body and outer protection tubes by pulling and unwinding the plastic support core in counter clockwise direction. Use of special tools is not necessary.

Detailed instructions for installing the 3M QS2000B Series Branch Joints are included in each kit.

Product Identification

3M™ QS2000B Series Branch Joint kits are marked with supplier name, cable cross section ranges, voltage class and cable type, storage conditions and manufacturing codes for product traceability.



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK

Product Selection

Kit Reference	Diameter over Primary Insulation (mm)	Cross Section (mm ²) 6.6/11(12) kV & 12/20(24) kV	Resin Pack recommendation
92-BV6210-1/C	22.3 – 33.2	95 – 300	Type 1402FR – Qty 6 packs

Storage

The shelf life of 3M™ QS2000B Series Branch Joints is specified as 3 years.

Temperature: - 40°C to +50°C

Performance Tests

3M™ QS2000B Branch Joint Series meets and exceeds the requirements of the European standard CENELEC HD 629.1 and IEC 60502-4. See Test Report No. D1256-0E

Product Stewardship

3M has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis of our philosophy and policies by which we assess the health and environmental information on our products and then take the appropriate steps to protect employee, the public health and the environment.

Customer Notice

3M encourages its customers and potential users of 3M products to review their applications for such products from the standpoint of human health and environmental quality. To help ensure that 3M products are not used in ways for which they were not intended or tested. 3M personnel are available to assist customers in dealing with ecological and product safety considerations.

Regulatory Status

3M™ QS2000B Series Branch Joints are not subject of the European WEEE and RoHS Directives but meet their requirements



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK