

Cable Abandonment Kits

Low Voltage Coldshrink Cable Abandonment Kit

For Cable Types: XLPE/PVC Insulation, Lead Sheath, Steel Wire Armour, PVC Sheathed. Also suitable for Shipwiring Cables, Rubber/GSWB
Up to and including 1.9/3.3kv. 1, 2, 3, and 4 Core Cables

Kits include Cold Shrink End Cap, PST, Armour continuity, tapes, and full instructions

ACCEPTED CABLE DIAMETER (mm)	KIT REFERENCE
12 -18	CSCAK/1
18 - 25	CSCAK/2
25 - 42	CSCAK/3
42 -55	CSCAK/4
56 -81	CSCAK/5

Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law. If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law. 3M is a trademark of the 3M Company. Printed in the UK. © 3M United Kingdom PLC, 2003