


DBY-6 Direct Bury Splice Kit 600 Volts



Application

Use part DBY-6, which includes a Scotchlok™ Y electrical spring connector, to electrically connect two or more pre-stripped copper wire ends in a pigtail application and moisture seal the connection for direct burial.

Wire

Common AWG wire combinations (copper wire only, solid or stranded).

2 – 3 #16	1 #18 to 1 – 2 #14
2 – 3 #14	1 #18 to 1 – 2 #12
2 #12	1 #16 to 1 – 2 #12
1 #14 to 1 #12	

See page two for complete table of UL Listed combinations.

Regulatory Agencies:

UL Listed as a Wire Connector System For Use With Underground Conductors.

UL File No. E102356

Tested per UL Standard 486D

CSA Certified as a Underground Cable Splicing Kit

CSA File No. LR91920

Tested per CSA Standard C22.2 No.198.2.

Engineering Specification:

The device, 3M Brand DBY-6 Direct Bury Splice Kit, shall splice and effectively moisture seal two or more conductors. The electrical connector shall be a Scotchlok™ Y. The device shall be installed per manufacture's instructions and all applicable codes. The device shall be UL Listed as a Wire Connector System For Use With Underground Conductors.


Construction:

Connector:	Steel spring, metal shell, flame retardant pvc insulator
Tube:	Polypropylene
Gel:	Silicone electrical insulating gel

Application Data:

Application Temperature:	32°F to 120°F (0°C to 49°C)
Operating Temperature:	221°F to -40°F (105°C to -40°C)
Voltage Rating:	600 Volts
Weight of one kit (2 splices):	.0612 lbs (27,92 gm)
Storage:	Do not store above 120°F (49°C)

NOT FOR USE IN DIRECT ULTRAVIOLET EXPOSURE







HOW TO READ THIS CHART

EXAMPLE 1

EXAMPLE 2: 1 No. 10 sol to
1 No. 16 str

EXAMPLE 2

1/2"
(12,7mm)



3M