



ITCSN

Heavy Wall Heat Shrink Tubing

Data Sheet



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
 TEL 0044 191 490 1547 FAX 0044 477 5371
 TEL 0044 117 977 4647 FAX 0044 977 5582
 WWW.THORNEANDDERRICK.CO.UK



LISTED
 98U1
 Wire connector
 system for use
 with underground
 connectors



LR 86335

Product Description

3M™ ITCSN Heat Shrink Tubing is designed to provide reliable performance for electrical splices, connections, and terminations, as well as mechanical and environmental protection. ITCSN is fabricated from cross-linked polyolefin. The tubing is highly split resistant, and fast shrinking to provide rapid installation. The tubing comes standard with a factory-applied adhesive/sealant.

Product Features

- Fast and easy installation
- Thick walls top resist puncture and abrasion damage
- Complete environmental protection
- Versatile, a minimum number of sizes cover the entire range of applications
- Shrink ratio as high as 4:1
- Resists acids and alkalies
- Bonds to a wide variety of substrates
- Reliable and proven
- UV resistant

Applications

- Primary electrical insulation for solid dielectric wire and cable rated to 1000 volts
- For indoor, outdoor or overhead use
- Direct buried or submersible
- Insulating secondary splices
- Shrink ratio as high as 4:1
- Physical protection and moisture sealing of high voltage air insulated connectors and lugs, such as lug connections to bus bars
- Relocation of service
- Dig-in repairs
- Sheath repairs

Product Selection

Selecting ITCSN tubing is easy and straightforward. The largest tubing size that provides a tight fit when fully recovered will produce the maximum wall thickness. Final wall thickness is proportional to the degree of tubing recovery.

Physical and Electrical Typical Properties

Property and Test Method	Typical Value*
Continuous Operating Temperature (less adhesive)	-55°C to 110°C
Color	Black
Shore D Hardness (ASTM D-2240)	42
Low Temperature Flexibility (4 hours @ -55°C)	No Cracking
Heat Shock (4 hours @ 255°C)	No Cracking, Flowing or Dripping
2% Secant Modulus (ASTM D-882 A)	14,000psi (98MPa)
Specific Gravity (ASTM D-792 A-1)	1.28
Water Absorption (ASTM D-570 6.1)	0.05%
Ultimate Elongation	475%
Longitudinal Change	+1, -10%
Dielectric Strength (60 mils) (ATSM D-149)	500 v/mil
Volume Resistivity (ATSM D-257)	1 x 10 ¹⁴ ohm cm
Fungus Resistance (ATSM G-21)	Non-nutrient
Corrosivity (Mil-I-23053/15)	Non-corrosive
Air-Oven Aging (7days@ 175°C)	
-Tensile Strength	2,680 psi (18 MPa)
-Elongation	375%
Ultimate Tensile Strength (ASTM D-412)	2400 psi (16 MPa)

*All values are averages, based on several determinations, and are not intended for specification purposes.

Engineering/Architectural Specifications

The tubing must be usable both indoors and outdoors, in overhead, direct-buried, or submerged applications on cables rated up to 1000 volts. It is not adversely affected by moisture, mild acids and alkalies, fuels, oils, ozone, or ultraviolet light. It must be compatible with and adhere to all types of cable jackets, including rubber, plastic or lead.

Physical and Electrical Typical Properties

Product Number	Cable Size Range	Minimum Expanded/ Maximum Recovered I.D.		Cable O.D. Use Range Maximum - Minimum		Certification and Listings	
ITCSN-0400	12 - 6 AWG (4 - 10 mm ²)	0.40 / 0.15"	10,2 / 3,8 mm	0.35 - 0.17"	9 - 3,3 mm	UL E102356	CS LR86335
ITCSN-0800	8 - 1/0 AWG (10 - 15 mm ²)	0.80 / 0.20"	20,3 / 5,1 mm	0.65 - 0.24"	18 - 5,6 mm	UL E102356	CS LR86335
ITCSN-01100	2 - 4/0 AWG (35 - 95 mm ²)	1.10 / 0.37"	27,9 / 9,4 mm	0.88 - 0.40"	24 - 9,4 mm	UL E102356	CS LR86335
ITCSN-1500	3/0 AWG - 400kcmil (95 - 185 mm ²)	1.50 / 0.50"	38,1 / 12,7 mm	1.19 - 0.60"	33 - 12,1 mm	UL E102356	CS LR86335
ITCSN-2000	250 - 750kcmil (150 - 300 mm ²)	2.00 / 0.65"	50,8 / 16,5 mm	1.60 - 0.75"	44,5 - 19,0 mm	UL E102356	CS LR86335
ITCSN-3000	600 - 1250kcmil (400 - 625 mm ²)	3.00 / 1.00"	76,2 / 25,4 mm	2.25 - 1.20"	63,5 - 25,4 mm		CS LR86335
ITCSN-4500	1500 - 2500kcmil (800 - 1000 mm ²)	4.50 / 1.50"	114,3 / 38,1 mm	4.00 - 1.50"	101,6 - 38,1 mm		
ITCSN-6000	2.1 - 4.8" (53 - 122 mm ²)	6.00 / 1.80"	152,4 / 45,7 mm	5.50 - 1.80"	139,7 - 45,7 mm		

Product Specifications

The heat shrink tubing must be chemically crosslinked, thermally stabilized polyolefin, capable of operation at cable emergency overload temperatures of 130°C. The tubing must have UL Listing (UL 486D, 600V) and be approved for the use. CSA Certified. Supplied tubing lengths of 4 feet and less shall be adhesive lined. The minimum shrink temperature shall be 250°F.

Performance Tests

UL 486D — ITCSN Tubing was subjected to the requirements of UL 486D and passed all tests. ITCSN is UL Listed per UL 486D. CSA Certified.

Availability

3M™ ITCSN Heat Shrink Tubing is available from your electrical distributor.

Maintenance

3M ITCSN Heat Shrink Tubing is not impaired by freezing or overheating due to ambient temperature found in storage or shipping. Normal storage and stock rotation is recommended.


Installation Techniques

Exact instructions are available on a separate sheet. the following is a summary of the instructions.

1. Thoroughly clean and prepare cable.
2. Slide 3M ITCSN onto cable.
3. Install connector, if applicable.
4. Center tubing.



5. Shrink tubing from center.



6. Heat until tubing is completely shrunk and adhesive/sealant (if applicable) is squeezed from ends.

3M is a trademark of 3M.



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

IMPORTANT NOTICE

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of 5 years from the date of manufacture. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the shelf life period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**



Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
www.3M.com/elpd



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK