



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

SX

Stainless Steel and Mild Steel Enclosures

SX Range

1

BPG Range

2

BPGA Range

3

ZAG Range

4

High Voltage

5

Fire Rated

6

ZP Range

7

Specials

8

Technical

9

Stainless Steel and Mild Steel Enclosures

1

SX Range

The SX range comprises 14 sizes of enclosure manufactured in either mild steel or stainless steel. 11 sizes are available in depths of 140 or 200mm and 8 sizes are available in depths of 140, 200 or 300mm. The majority of the range can be fitted with removable gland plates on any or all of the four sides. The mild steel version (MSX) is available with a number of paint options (most RAL colours are available) and anti-corrosion finishes. Further advice on surface finishes can be sought from the ABTECH sales office.



The stainless steel range (SSX) is manufactured in 316 grade stainless steel to give the maximum environmental protection. The main body is manufactured from 2mm thick sheet and the mounting straps and gland plates from 3mm thick plate. Cable entries can be drilled in the enclosure door or sides or through the gland plates, if fitted. Entries may also be drilled through the rear face of the enclosure (EEEx'e' versions also.)

Another important feature of the SX range is the hinged, lift-off door, which is held to the enclosure by at least 4 captive stainless steel screws, which also maintain the correct compression on the gasket. The hinges are solid block, machined oversize to enable the screws to control the closing of the door, not the hinge, its only function being to support the door when opened. The hinges allow easy removal of the door with only minimal opening required before removal (less than 10°).

Earthing is accomplished by means of an Internal / external earth stud fitted as standard which can be connected to the terminal mounting rail or component mounting plate. Optionally, earth studs can be fitted to the door and gland plates. Rail mounted earth terminals or proprietary earth bars can be fitted inside the enclosure and ABTECH Sales staff will be happy to advise on this. When fitted with a standard neoprene gasket, the enclosure is suitable for ambient temperatures of - 40°C to + 80°C. Alternatively, when fitted with an optional silicone gasket the temperature range is increased to - 70°C to + 130°C.

The SX range of enclosures are suitable for use in hazardous areas and can be supplied with a number of certificates. ATEX EEEx'e' to BS EN 50019 (Zone 1 & 2) EEEx'nA' to BS EN50021 (Zone 2) and NEMA 4X (CSA, UL & FM class 1, div 2) and GOST.



The SX range can be supplied fitted with any component approved terminal to apparatus level or can be supplied empty as component approved for the clients own certification requirements.


The SX range was specifically designed to meet the rigours of the North Sea environment and is capable of achieving IP66 and IP67. It has also undergone and passed the Shell/ERA deluge test which was devised to adequately test enclosures and electrical equipment which is routinely subjected to ships deck conditions or fire deluge systems.

IP68 enclosures are also available for depths up to 120 ft to special order. Further information on submersible enclosures is available in Section 8 of this catalogue.



The SX range has many features which lend itself to a wide variety applications, not least of which is the ability to be constructed to almost any dimension due to its fabricated nature. This can also be applied to EEx'e' enclosures where the certification allows oversize enclosures to be manufactured whilst retaining the next smallest sized enclosure's power rating.

The SX range is also suitable for fire resistance applications and when fitted with ceramic terminals meets the requirements of IEC 331 (750°C for 3 hours) and also BS6387/1983 (950°C for 3 hours). Further details are available in Section 6 of this catalogue.



Other applications include junction boxes, both industrial and hazardous area, OEM applications, fire protection systems, tunnel wiring, IP68 applications, etc.

SX Range Features

- Wide Operating Temperature (- 70°C to + 130°C)
- Ingress Protection up to IP68
- Fire Resistant to IEC331
- Impact Resistant > 10 Nm
- Corrosion Resistant
- Gland plates can be fitted to any or all four sides (size SX0 and above)
- Certification for use in Zone 1 and 2
- UL, CSA, ATEX and GOST Approvals
- Ideal for Petrochemical and Marine applications

SX Range

1

BPG Range

2

BPGA Range

3

ZAG Range

4

High Voltage

5

Fire Rated

6

ZP Range

7

Specials

8

Technical

9

Stainless Steel and Mild Steel Enclosures

Accessories and Options

1

SX Range

The following table is a list of the available accessories suitable for particular standard sizes of SX enclosures. Care should be taken when ordering accessories for use with enclosures intended for hazardous areas to ensure that compliance with certification is retained.

Part Number (see note 1)	Width (mm) (see note 2)	Height (mm) (see note 2)	Depth (mm) (see note 2)	140mm Depth	200mm Depth	300mm Depth	Gland Plates (on any or all four sides)	EP – Electro-polished external surfaces (SX range only)	LB - Label Bracket Welded to Door	ES - Earth Stud fitted to Door and Gland Plates	EB - Internal Earthing Bar	SIL - Silicone Gasket (see note 3)	BD - Breather Drain (see note 4)	TP - Tamper Proof Lid Fixing Screws	MP - Component Mounting Plate (Steel/Stainless Steel)	RF – RFI Protection (see note 5)
SX45	114	114	51	✗	✗	✗	✗	✓	✓	✗	✗	✓	✓	✓	✓	✓
SX64	102	152	63	✗	✗	✗	✗	✓	✓	✗	✗	✓	✓	✓	✓	✓
SX66	152	152	102	✗	✗	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX0	152	229	-	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX0.5	184	274	-	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX1	234	324	-	✓	✓	✗	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX1.5	306	306	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX2	372	324	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX3	372	448	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX4	372	510	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX5	510	510	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX6	510	780	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX7	650	950	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SX8	800	1250	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Ordering Example;

SX1.5 300 4GP LB EB

(Stainless Steel SX1.5 300mm deep, 4 gland plates, label bracket on door and internal earthing bar)

1. The range is available either in stainless steel 316 (SX variants) or mild steel (MSX variants).
2. Manufacturing tolerances are +/- 3mm on overall dimensions and +/- 0.5mm on fixing hole centres.
3. Silicone gasket increases temperature rating (-70° to +130° C) and may increase working life in some applications.
4. Breather drain available in IP66 stainless steel or plastic.
5. Radio Frequency Interference (RFI) gasket may reduce IP rating.


Stainless Steel and Mild Steel Enclosures



Full width, full height Gland Plates
(can be fitted to any or all sides)




Earth Stud fitted to door and gland plates




Label Bracket
(welded to door)



Electro-polished
(external surfaces on SX range only)



Internal Earthing bar
(can be fitted with clamps)



Component Mounting Plate
(steel or stainless steel 316)

SX Range

1

BPG Range

2

BPGA Range

3

ZAG Range

4

High Voltage

5

Fire Rated

6

ZP Range

7


Specials

8

Technical

9


MSX 45 / SSX 45 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

MSX 45 / SSX 45 Specifications			Terminal Populations			Entry Matrix				
Width	114mm		Maximum Number of Rows		1	Entry Size	Side A-C	Side B-D		
Length	114mm		Weidmuller		Wago		M16	4	4	
Depth	51mm		SAK 2.5		7	280-992	M20	2	2	
Material	Mild steel		SAK 4		7	280-999	M25	2	2	
	Stainless steel 316 (1.4404)		SAK 6		5	281-691	M32	0	0	
			SAK 10 *		4	281-992	M40	0	0	
Weight	1200g		SAK 16 *		3	281-993	Drilling Envelope			
IP Rating	66 or 67		SAK 35		0	282-691	Side A-C	114 x 51mm		
Temperature	-40° to 80° C (standard neoprene gasket)		SAK 70		0	284-691	Side B-D	114 x 51mm		
	-70° to 130° C (silicone gasket)					285-691				
	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7					280-998				
ATEX EEx nA (Zone 2) BS EN 60079-15					281-998					
Certification	ATEX EEx nR (Zone 2) BS EN 60079-15		Phoenix			264-120	SX 45 Photo 			
	CSA - Ex e (Class 1 Zone 1 & Zone 2)		UK 2.5 N		9	264-132 (2)				
	FM - AEx e (Class 1 Zone 1 & Zone 2)		UK 3 N		9	264-134 (4)				
	GOST-R Ex e (Zone 1 & Zone 2)		UK 5 N		7	262-132 (2)				
	NEMA 4X (CSA, UL & FM) (class 1 division 2)		UK 10 N *		4	262-134 (4)				
			UK 16 N *		3					
Power Rating	8.0W		UK 35 N		0					
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.										

MSX 64 / SSX 64 Drawing




All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

MSX 64 / SSX 64 Specifications				Terminal Populations				Entry Matrix		
Width	102mm	Maximum Number of Rows		1		Entry Size	Side A-C	Side B-D		
Length	152mm	Weidmuller		Wago		M16	6	8		
Depth	63mm	SAK 2.5	15	280-992	18	M20	3	4		
Material	Mild steel	SAK 4	15	280-999	0	M25	2	3		
	Stainless steel 316 (1.4404)	SAK 6	11	281-691	15	M32	1	2		
	1500g	SAK 10 *	9	281-992	15	M40	0	0		
	66 or 67	SAK 16 *	0	281-993	0	Drilling Envelope				
IP Rating		SAK 35	0	282-691	0	Side A-C	102 x 63mm			
Temperature	-40° to 80° C (standard neoprene gasket)	SAK 70	0	284-691	0	Side B-D	152 x 63mm			
				283-691	0					
	-70° to 130° C (silicone gasket)			285-691	0					
		ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7			280-998	18				
Certification	ATEX EEx nA (Zone 2) BS EN 60079-15			281-998	15	SX 64 Photo				
	ATEX EEx nR (Zone 2) BS EN 60079-15			264-120	15					
		CSA - Ex e (Class 1 Zone 1 & Zone 2)	Phoenix		264-220	9				
		FM - AEx e (Class 1 Zone 1 & Zone2)	UK 2.5 N	17	264-132 (2)	3				
GOST-R Ex e (Zone 1 & Zone 2)		UK 3 N	17	264-134 (4)	2					
NEMA 4X (CSA, UL & FM) (class 1 division 2)		UK 5 N	15	262-132 (2)	3					
Power Rating	10.258W		UK 10 N *	9	262-134 (4)	2				
			UK 16 N *	7						
			UK 35 N	0						
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.										

Technical	9	Specials	8	Fire Rated	6	High Voltage	5	ZAG Range	4	BPGA Range	3	BPG Range	2	SX Range	1
-----------	---	----------	---	------------	---	--------------	---	-----------	---	------------	---	-----------	---	----------	---

MSX 66 / SSX 66 Drawing






All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

MSX 66 / SSX 66 Specifications			Terminal Populations			Entry Matrix		
Width	152mm		Maximum Number of Rows		1	Entry Size	Side A-C	Side B-D
Length	152mm		Weidmuller		Wago		14	14
Depth	102mm		SAK 2.5	15	280-992	18	8	8
Material	Mild steel		SAK 4	15	280-999	18	6	6
	Stainless steel 316 (1.4404)		SAK 6	11	281-691	15	3	3
Weight	2200g		SAK 10 *	9	281-992	15	2	2
IP Rating	66 or 67		SAK 16 *	7	281-993	15	Drilling Envelope	
Temperature	-40° to 80° C (standard neoprene gasket)		SAK 35 *	6	282-691	11	Side A-C	152 x 102mm
	-70° to 130° C (silicone gasket)		SAK 70	0	284-691	10	Side B-D	152 x 102mm
					283-691	7		
Certification	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7				285-691	0		
	ATEX EEx nA (Zone 2) BS EN 60079-15				280-998	18		
	ATEX EEx nR (Zone 2) BS EN 60079-15				281-998	15		
	CSA - Ex e (Class 1 Zone 1 & Zone 2)		Phoenix		264-120	16	SX 66 Photo 	
	FM - AEx e (Class 1 Zone 1 & Zone2)		UK 2.5 N	17	264-132 (2)	3		
	GOST-R Ex e (Zone 1 & Zone 2)		UK 3 N	17	264-134 (4)	2		
Power Rating	NEMA 4X (CSA, UL & FM) (class 1 division 2)		UK 5 N	14	262-132 (2)	3	* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.	
	14.287W		UK 10 N *	9	262-134 (4)	2		
			UK 16 N *	7				
			UK 35 N *	6				

SX Range
1BPG Range
2BPGA Range
3ZAG Range
4High Voltage
5Fire Rated
6ZP Range
7Specials
8Technical
9

MSX 0 / SSX 0 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

MSX 0 / SSX 0 Specifications			
Width	152mm		
Length	229mm		
Depth	140mm or 200mm		
Material	Mild steel		
	Stainless steel 316 (1.4404)		
Weight	140mm deep 2200g	200mm deep 4000g	
	66 or 67		
IP Rating	-40° to 80° C (standard neoprene gasket)		
Temperature	-70° to 130° C (silicone gasket)		
	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7		
Certification	ATEX EEx nA (Zone 2) BS EN 60079-15		
	ATEX EEx nR (Zone 2) BS EN 60079-15		
	CSA - Ex e (Class 1 Zone 1 & Zone 2)		
	FM - AEx e (Class 1 Zone 1 & Zone2)		
Power Rating	GOST-R Ex e (Zone 1 & Zone 2)		
	NEMA 4X (CSA, UL & FM) (class 1 division 2)		
	19.874W		

Terminal Populations			
Maximum Number of Rows	1		
Weidmuller	Wago		
SAK 2.5	21	280-992	24
SAK 4	19	280-999	24
SAK 6	16	281-691	20
SAK 10 *	12	281-992	20
SAK 16 *	10	281-993	20
SAK 35 *	7	282-691 *	15
SAK 70 *	5	284-691 *	12
		283-691	0
		285-691	0
		280-998	24
		281-998	20
		264-120	21
Phoenix			
UK 2.5 N	25	264-132 (2)	4
UK 3 N	25	264-134 (4)	3
UK 5 N	21	262-132 (2)	4
UK 10 N *	12	262-134 (4)	3
UK 16 N *	10		
UK 35 N *	8		
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.			


Entry Matrix		
Entry Size	Side A-C	Side B-D
M16	5	9
M20	3	6
M25	2	3
M32	1	2
M40	1	2
Drilling Envelope		
Side A-C	87 x 75mm (4 x gp 140)	
Side B-D	144 x 75mm (4 x gp 140)	



SX 0 Photo



MSX 0.5 / SSX 0.5 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

Entry Matrix		
Entry Size	Side A-C	Side B-D
M16	7	12
M20	4	8
M25	2	4
M32	2	3
M40	1	2
Drilling Envelope		
Side A-C	119 x 75mm (4 x gp 140)	
Side B-D	189 x 75mm (4 x gp 140)	



SX 0.5 Photo



Terminal Populations			
Maximum Number of Rows	2		
Weidmuller	Wago		
SAK 2.5	56	280-992	31
SAK 4	52	280-999	31
SAK 6	42	281-691	27
SAK 10 *	34	281-992	27
SAK 16 *	14	281-993	27
SAK 35 *	10	282-691 *	21
SAK 70 *	7	284-691 *	16
		283-691	28
		285-691	0
		280-998	31
		281-998	27
		264-120	56
Phoenix			
		264-220	32
UK 2.5 N	68	264-132 (2)	12
UK 3 N	68	264-134 (4)	8
UK 5 N	56	262-132 (2)	12
UK 10 N *	34	262-134 (4)	8
UK 16 N *	14		
UK 35 N *	11		

* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.

MSX 0.5 / SSX 0.5 Specifications		
Width	184mm	
Length	274mm	
Depth	140mm or 200mm	
Material	Mild steel	
	Stainless steel 316 (1.4404)	
Weight	140mm deep 5000g	200mm deep 6000g
IP Rating	66 or 67	
Temperature	-40° to 80° C (standard neoprene gasket)	
	-70° to 130° C (silicone gasket)	
Certification	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7	
	ATEX EEx nA (Zone 2) BS EN 60079-15	
	ATEX EEx nR (Zone 2) BS EN 60079-15	
	CSA - Ex e (Class 1 Zone 1 & Zone 2)	
	FM - AEx e (Class 1 Zone 1 & Zone2)	
	GOST-R Ex e (Zone 1 & Zone 2)	
Power Rating	NEMA 4X (CSA, UL & FM) (class 1 division 2)	
	19.874W	

Technical

9

Specials

8

ZP Range

7

Fire Rated

6

High Voltage

5

ZAG Range

4

BPGA Range

3


BPG Range

2

SX Range

1

MSX 1 / SSX 1 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

Stainless Steel and Mild Steel Enclosures

MSX 1 / SSX 1 Specifications				Terminal Populations				Entry Matrix			
Width	234mm			Maximum Number of Rows		2		Entry Size	Side A-C	Side B-D	
Length	324mm			Weidmuller		Wago		M16	10	14	
Depth	140mm or 200mm			SAK 2.5		72	280-992	M20	7	10	
Material	Mild steel			SAK 4		66	280-999	M25	4	6	
	Stainless steel 316 (1.4404)			SAK 6		54	281-691	M32	2	4	
	140mm deep 6300g			SAK 10 *		44	281-992	M40	2	3	
Weight	200mm deep 7200g			SAK 16 *		18	281-993	Drilling Envelope			
IP Rating	66 or 67			SAK 35 *		14	282-691	Side A-C	169 x 75mm (4 x gp 140)		
Temperature	-40° to 80° C (standard neoprene gasket)			SAK 70 *		10	284-691 *	Side B-D	239 x 75mm (4 x gp 140)		
	-70° to 130° C (silicone gasket)										
	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7										
Certification	ATEX EEx nA (Zone 2) BS EN 60079-15										
	ATEX EEx nR (Zone 2) BS EN 60079-15			Phoenix			264-120				
	CSA - Ex e (Class 1 Zone 1 & Zone 2)			UK 2.5 N		86	264-132 (2)				
	FM - AEx e (Class 1 Zone 1 & Zone2)			UK 3 N		86	264-134 (4)				
	GOST-R Ex e (Zone 1 & Zone 2)			UK 5 N		72	262-132 (2)				
Power Rating	NEMA 4X (CSA, UL & FM) (class 1 division 2)			UK 10 N *		44	262-134 (4)				
	29.206W			UK 16 N *		18					
				UK 35 N *		14					
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.											

ABTECH

A

B

C

D

Side A-C

Side B-D

Drilling Envelope


169 x 75mm (4 x gp 140)

239 x 75mm (4 x gp 140)

SX 1 Photo



MSX 1.5 / SSX 1.5 Drawing



All **blue** dimensions in mm, all **green** dimensions in decimal inches (drawing not to scale)

Stainless Steel and Mild Steel Enclosures

Entry Matrix			
Entry Size	Side A-C	Side B-D	
M16	14	12	
M20	10	10	
M25	6	5	
M32	4	3	
M40	3	3	

Drilling Envelope			
Side A-C	241 x 75mm (4 x gp 140)		
Side B-D	221x 75mm (4 x gp 140)		



SX 1.5 Photo



Terminal Populations			
Maximum Number of Rows		3	
Weidmuller		Wago	
SAK 2.5	99	280-992	74
SAK 4	93	280-999	74
SAK 6	75	281-691	64
SAK 10 *	60	281-992	64
SAK 16 *	34	281-993	64
SAK 35 *	24	282-691	48
SAK 70 *	20	284-691 *	38
		283-691 *	32
		285-691 *	11
		280-998	74
		281-998	64
		264-120	99
Phoenix		264-220	60
UK 2.5 N	120	264-132 (2)	21
UK 3 N	120	264-134 (4)	15
UK 5 N	99	262-132 (2)	21
UK 10 N *	60	262-134 (4)	15
UK 16 N *	34		
UK 35 N *	26		
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.			

MSX 1.5 / SSX 1.5 Specifications			
Width	306mm		
Length	306mm		
Depth	140mm or 200mm		
Material	Mild steel		
	Stainless steel 316 (1.4404)		
Weight	140mm deep	200mm deep	
	7300g	8800g	
IP Rating	66 or 67		
Temperature	-40° to 80° C		
	(standard neoprene gasket)		
	-70° to 130° C		
	(silicone gasket)		
Certification	ATEX EEx e (Zone 1 & Zone 2)		
	BS EN 60079-7		
	ATEX EEx nA (Zone 2)		
	BS EN 60079-15		
	ATEX EEx nR (Zone 2)		
	BS EN 60079-15		
	CSA - Ex e (Class 1 Zone 1 & Zone 2)		
	FM - AEx e (Class 1 Zone 1 & Zone2)		
	GOST-R Ex e (Zone 1 & Zone 2)		
	NEMA 4X (CSA, UL & FM)		
	(class 1 division 2)		
Power Rating	32.284W		

SX Range

1

BPG Range

2

BPGA Range

3

ZAG Range

4

High Voltage

5

Fire Rated

6

ZP Range

7


Specials

8

Technical

9

MSX 2 / SSX 2 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)


Stainless Steel and Mild Steel Enclosures

MSX 2 / SSX 2 Specifications				Terminal Populations			Entry Matrix			
Width	372mm			Maximum Number of Rows		3	Entry Size	Side A-C	Side B-D	
Length	324mm			Weidmuller		Wago		M16	18	14
Depth	140mm or 200mm			SAK 2.5	132	280-992	150	M20	14	10
Material	Mild steel			SAK 4	123	280-999	150	M25	7	6
	Stainless steel 316 (1.4404)			SAK 6	99	281-691	126	M32	5	4
	140mm deep	200mm deep		SAK 10	78	281-992	126	M40	4	3
Weight	9.5Kg	11.3Kg		SAK 16	66	281-993	84	Drilling Envelope		
IP Rating	66 or 67			SAK 35	42	282-691	99	Side A-C	307 x 75mm (4 x gp 140)	
	-40° to 80° C (standard neoprene gasket)			SAK 70	24	284-691 *	78	Side B-D	239x 75mm (4 x gp 140)	
	-70° to 130° C (silicone gasket)					283-691 *	44			
Temperature	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7					285-691 *	30			
	ATEX EEx nA (Zone 2) BS EN 60079-15					280-998	150			
	ATEX EEx nR (Zone 2) BS EN 60079-15					281-998	126			
Certification						264-120	132	SX 2 Photo 		
				Phoenix		264-220	78			
				UK 2.5 N	156	264-132 (2)	27			
				UK 3 N	156	264-134 (4)	18			
				UK 5 N	132	262-132 (2)	27			
Power Rating				UK 10 N	78	262-134 (4)	18	* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.		
				UK 16 N	66					
				UK 35 N	54					
				36.500W						

Drilling Envelope

Side A-C 307 x 75mm (4 x gp 140)

Side B-D 239x 75mm (4 x gp 140)



SX 2 Photo



Technical

9

Specials

8

ZP Range

7

Fire Rated

6

High Voltage

5

ZAG Range

4

BPGA Range

3


BPG Range

2

SX Range

1

MSX 3 / SSX 3 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)


MSX 3 / SSX 3 Specifications				Terminal Populations			Entry Matrix					
Width	372mm			Maximum Number of Rows		3	Entry Size	Side A-C	Side B-D			
Length	448mm			Weidmuller		Wago		M16	18	20		
Depth	140mm or 200mm			SAK 2.5	168	280-992	189	M20	14	16		
Material	Mild steel			SAK 4	156	280-999	189	M25	7	9		
	Stainless steel 316 (1.4404)			SAK 6	126	281-691	162	M32	5	6		
	140mm deep	200mm deep		SAK 10 *	102	281-992	162	M40	4	5		
Weight	11.3Kg	13.3Kg		SAK 16 *	84	281-993	108	Drilling Envelope				
IP Rating	66 or 67			SAK 35 *	63	282-691	126	Side A-C	307 x 75mm (4 x gp 140)			
Temperature	-40° to 80° C (standard neoprene gasket)			SAK 70 *	45	284-691 *	99	Side B-D	363 x 75mm (4 x gp 140)			
	-70° to 130° C (silicone gasket)					283-691 *	56					
						285-691 *	38					
	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7					280-998	189					
	ATEX EEx nA (Zone 2) BS EN 60079-15					281-998	162					
	ATEX EEx nR (Zone 2) BS EN 60079-15					264-120	168					
	Certification	CSA - Ex e (Class 1 Zone 1 & Zone 2)				Phoenix		264-220	99	SX 3 Photo		
FM - AEx e (Class 1 Zone 1 & Zone2)				UK 2.5 N	201	264-132 (2)	36					
GOST-R Ex e (Zone 1 & Zone 2)				UK 3 N	201	264-134 (4)	24					
NEMA 4X (CSA, UL & FM) (class 1 division 2)				UK 5 N	168	262-132 (2)	36					
Power Rating		42.289W				UK 10 N *	102	262-134 (4)	24			
						UK 16 N *	84					
				UK 35 N *	69							
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.												

* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.

Drilling Envelope

Side A-C 307 x 75mm (4 x gp 140)

Side B-D 363 x 75mm (4 x gp 140)



SX 3 Photo



Technical

Specials

ZP Range

Fire Rated

High Voltage


ZAG Range

BPGA Range

BPG Range

SX Range

MSX 4 / SSX 4 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

Entry Matrix		
Entry Size	Side A-C	Side B-D
M16	18	24
M20	14	20
M25	7	10
M32	5	7
M40	4	6
Drilling Envelope		
Side A-C	307 x 75mm (4 x gp 140)	
Side B-D	425 x 75mm (4 x gp 140)	



Terminal Populations			
Maximum Number of Rows	3		
Weidmuller	Wago		
SAK 2.5	198	280-992	222
SAK 4	183	280-999	222
SAK 6	150	281-691	189
SAK 10	120	281-992	189
SAK 16	99	281-993	126
SAK 35	75	282-691	147
SAK 70	54	284-691	117
		283-691	66
		285-691	44
		280-998	222
		281-998	189
		264-120	198
Phoenix	117		
UK 2.5 N	237	264-132 (2)	42
UK 3 N	237	264-134 (4)	30
UK 5 N	198	262-132 (2)	42
UK 10 N	102	262-134 (4)	30
UK 16 N	99		
UK 35 N	81		

* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.

MSX 4 / SSX 4 Specifications			
Width	372mm		
Length	510mm		
Depth	140mm or 200mm		
Material	Mild steel		
	Stainless steel 316 (1.4404)		
Weight	140mm deep	200mm deep	
	12.7Kg	14.8Kg	
IP Rating	66 or 67		
Temperature	-40° to 80° C (standard neoprene gasket)		
	-70° to 130° C (silicone gasket)		
Certification	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7		
	ATEX EEx nA (Zone 2) BS EN 60079-15		
	ATEX EEx nR (Zone 2) BS EN 60079-15		
	CSA - Ex e (Class 1 Zone 1 & Zone 2)		
	FM - AEx e (Class 1 Zone 1 & Zone2)		
	GOST-R Ex e (Zone 1 & Zone 2)		
Power Rating	NEMA 4X (CSA, UL & FM) (class 1 division 2)		
	44.726W		

Technical

9

Specials

8

ZP Range

7

Fire Rated

6

High Voltage

5

ZAG Range

4

BPGA Range

3


BPG Range

2

SX Range

1

MSX 5 / SSX 5 Drawing




All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

Stainless Steel and Mild Steel Enclosures

Entry Matrix			
Entry Size	Side A-C	Side B-D	
M16	26	24	
M20	20	20	
M25	10	10	
M32	7	7	
M40	6	6	

Drilling Envelope

Side A-C	445 x 75mm (4 x gp 140)
Side B-D	425 x 75mm (4 x gp 140)



SX 5 Photo




Terminal Populations			
Maximum Number of Rows	Wago		
4			
Weidmuller			
SAK 2.5	264	280-992	296
SAK 4	244	280-999	296
SAK 6	200	281-691	252
SAK 10	160	281-992	252
SAK 16	132	281-993	189
SAK 35	100	282-691	196
SAK 70	72	284-691	156
		283-691	99
		285-691	66
		280-998	296
		281-998	252
		264-120	264
Phoenix			
		264-220	156
UK 2.5 N	316	264-132 (2)	56
UK 3 N	316	264-134 (4)	40
UK 5 N	264	262-132 (2)	56
UK 10 N	160	262-134 (4)	40
UK 16 N	132		
UK 35 N	108		
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.			

MSX 5 / SSX 5 Specifications			
Width	510mm		
Length	510mm		
Depth	140mm or 200mm		
Material	Mild steel		
	Stainless steel 316 (1.4404)		
Weight	140mm deep	200mm deep	
	17.0Kg	20.0Kg	
IP Rating	66 or 67		
Temperature	-40° to 80° C		
	(standard neoprene gasket)		
	-70° to 130° C		
	(silicone gasket)		
Certification	ATEX EEx e (Zone 1 & Zone 2)		
	BS EN 60079-7		
	ATEX EEx nA (Zone 2)		
	BS EN 60079-15		
	ATEX EEx nR (Zone 2)		
	BS EN 60079-15		
	CSA - Ex e (Class 1 Zone 1 & Zone 2)		
	FM - AEx e (Class 1 Zone 1 & Zone2)		
	GOST-R Ex e (Zone 1 & Zone 2)		
	NEMA 4X (CSA, UL & FM)		
Power Rating	(class 1 division 2)		
	50.328W		

SX Range
1BPG Range
2BPGA Range
3ZAG Range
4High Voltage
5Fire Rated
6ZP Range
7Specials
8Technical
9


MSX 6 / SSX 6 Drawing




All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

Stainless Steel and Mild Steel Enclosures


MSX 6 / SSX 6 Specifications				Terminal Populations			Entry Matrix		
Width	510mm			Maximum Number of Rows	4		Entry Size	Side A-C	Side B-D
Length	780mm			Weidmuller	Wago		M16	26	40
Depth	140mm or 200mm or 300mm			SAK 2.5	440	280-992	M20	20	34
Material	Mild steel			SAK 4	404	280-999	M25	11	18
	Stainless steel 316 (1.4404)			SAK 6	332	281-691	M32	7	11
	140mm 24.0kg	200mm 27.0kg	300mm 32.0kg	SAK 10	264	281-992	M40	6	9
IP Rating	66 or 67			SAK 16	220	281-993	Drilling Envelope		
Temperature	-40° to 80° C (standard neoprene gasket)			SAK 35	168	282-691	Side A-C	445 x 75mm (4 x gp 140)	
	-70° to 130° C (silicone gasket)			SAK 70	120	284-691	Side B-D	695 x 75mm (4 x gp 140)	
	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7					283-691			
ATEX EEx nA (Zone 2) BS EN 60079-15					285-691				
ATEX EEx nR (Zone 2) BS EN 60079-15					280-998				
Certification	FM - AEx e (Class 1 Zone 1 & Zone2)					281-998			
	GOST-R Ex e (Zone 1 & Zone 2)					264-120			
	NEMA 4X (CSA, UL & FM) (class 1 division 2)					264-220			
	57.383W					264			
						264-132 (2)			
Power Rating						92			
						64			
						64			
						92			
						64			


SX Range
1BPG Range
2BPGA Range
3ZAG Range
4High Voltage
5Fire Rated
6ZP Range
7Specials
8Technical
9

MSX 7 / SSX 7 Drawing




All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

MSX 7 / SSX 7 Specifications				Terminal Populations			Entry Matrix		
Width	650mm			Maximum Number of Rows		5	Entry Size	Side A-C	Side B-D
Length	950mm			Weidmuller		Wago	M16	34	81
Depth	140mm or 200mm or 300mm			SAK 2.5		685	280-992	28	60
Material	Mild steel			SAK 4		635	280-999	13	39
	Stainless steel 316 (1.4404)			SAK 6		520	281-691	10	28
	140mm 35.0kg	200mm 39.0kg	300mm 52.0kg	SAK 10		415	281-992	8	16
IP Rating	66 or 67			SAK 16		345	281-993	Drilling Envelope	
Temperature	-40° to 80° C (standard neoprene gasket)			SAK 35		260	282-691	585 x 75mm (4 x gp 140)	865 x 75mm (4 x gp 140)
	-70° to 130° C (silicone gasket)			SAK 70		150	284-691		
Certification	ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7						283-691		
	ATEX EEx nA (Zone 2) BS EN 60079-15						285-691		
	ATEX EEx nR (Zone 2) BS EN 60079-15						280-998		
	CSA - Ex e (Class 1 Zone 1 & Zone 2)						281-998		
	FM - AEx e (Class 1 Zone 1 & Zone2)						264-120		
Power Rating	GOST-R Ex e (Zone 1 & Zone 2)			Phoenix			264-220	SX 7 Photo	
	NEMA 4X (CSA, UL & FM) (class 1 division 2)			UK 2.5 N		820	264-132 (2)		
	68.000W			UK 3 N		820	264-134 (4)		
				UK 5 N		685	262-132 (2)		
				UK 10 N		415	262-134 (4)		
				UK 16 N		345			
				UK 35 N		280			
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.									



MSX 8 / SSX 8 Drawing



All blue dimensions in mm, all green dimensions in decimal inches (drawing not to scale)

MSX 8 / SSX 8 Specifications				Terminal Populations			Entry Matrix		
Width	800mm			Maximum Number of Rows	5		Entry Size	Side A-C	Side B-D
Length	1250mm			Weidmuller	Wago		M16	42	66
Depth	140mm or 200mm or 300mm			SAK 2.5	1295	280-992	M20	36	58
Material	Mild steel			SAK 4	635	280-999	M25	18	30
	Stainless steel 316 (1.4404)			SAK 6	520	281-691	M32	12	20
	140mm 40.0kg	200mm 52.0kg	300mm 59.0kg	SAK 10	415	281-992	M40	10	17
IP Rating	66 or 67			SAK 16	345	281-993	Drilling Envelope		
Temperature	-40° to 80° C (standard neoprene gasket)			SAK 35	260	282-691	Side A-C	735 x 75mm	
	-70° to 130° C (silicone gasket)			SAK 70	150	284-691	Side B-D	1165 x 75mm	
		ATEX EEx e (Zone 1 & Zone 2) BS EN 60079-7					283-691		
ATEX EEx nA (Zone 2) BS EN 60079-15						285-691			
ATEX EEx nR (Zone 2) BS EN 60079-15						280-998			
CSA - Ex e (Class 1 Zone 1 & Zone 2)						281-998			
FM - AEx e (Class 1 Zone 1 & Zone 2)						264-120			
Certification				Phoenix	264-220				
				UK 2.5 N	820	264-132 (2)			
				UK 3 N	820	264-134 (4)			
				UK 5 N	685	262-132 (2)			
				UK 10 N	415	262-134 (4)			
Power Rating				UK 16 N	345				
				UK 35 N	280				
	119.462W								
* Care must be taken to ensure that the size of this enclosure can accommodate the cable bending radius.									

SX Range

1

BPG Range

2

BPGA Range

3

ZAG Range

4

High Voltage

5

Fire Rated

6

ZP Range

7

Specials

8

Technical

9



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS
FURSE EARTHING
www.cablejoints.co.uk
Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371
Tel 0044 117 977 4647 Fax 0044 117 9775582

