




# ALROC - MV - Case CMF2/40NP - CMF2/60NP

ISO 9001


BUREAU VERITAS  
Certification



**MF2/40 - MF2/60**




Outer sheath



Insulation

**ASC R1E - ASC R2**



Bonded  
semi-conductor

C  
M  
F  
2/  
NP

ALROC

## FUNCTIONS

The CMF2/40 NP and CMF2/60 NP allow to remove cables outer sheath, bonded semi-conductor and insulation.

## CHARACTERISTICS

- ☞ Outer sheath
- ☞ Bonded semi-conductor
- ☞ Insulation

CMF2/NP  
CHOICE

| Model        | CMF2/40NP                          | CMF2/60NP                          |
|--------------|------------------------------------|------------------------------------|
| MF2 Diameter | 16 - 40 mm                         | 16 - 58 mm                         |
| ASC Diameter | 18 - 44 mm                         | 20 - 58 mm                         |
| Sections     | 25 <sup>2</sup> - 240 <sup>2</sup> | 50 <sup>2</sup> - 630 <sup>2</sup> |
| Weight       | 2,700 Kg                           | 3,200 Kg                           |



WWW.CABLEJOINTS.CO.UK  
THORNE & DERRICK UK  
TEL 0044 191 490 1547 FAX 0044 477 5371  
TEL 0044 117 977 4647 FAX 0044 977 5582  
WWW.THORNEANDDERRICK.CO.UK