

Head and eyes protection

Insulating rubber gloves

Insulating mats and platforms

Arc flash equipment

Equipment for working on pole

In many countries regulations have been established to protect workers from electrical shock and flash hazards in specific areas within which arc flash protection is required. These equipment must be used with insulating gloves and leather overgloves. Equipment up to 100 cal/cm<sup>2</sup> on request.

In compliance with NFPA 70E and ASTM Standards. FR - Flame Retardant garments.

### Arc flash face shield kit (10 cal/cm<sup>2</sup>)

Composition of the kit:

- 1 Face shield with chin cup 10 cal/cm<sup>2</sup>, absorbs > 99.9% of harmful UV radiation, 70% light transmission, tested to ASTM F2178 specifications
- 1 ABS helmet electrically insulated EN397, EN 50365, ANSI Z89.1 20kV.
- 1 carrying bag for face shield and helmet



**KIT-ARC-01** Weight: 1.5 kg

### Arc flash jacket and protective coverall kits (8 or 10 cal/cm<sup>2</sup>)

Composition of the kit:

- 1 Face shield with chin cup 10 cal/cm<sup>2</sup>, absorbs > 99.9% of harmful UV radiation, tested to ASTM F2178 specifications
- 1 ABS helmet electrically insulated EN397, EN 50365, ANSI Z89.1, 20kV.
- 1 safety glasses EN 166/EN 170
- 1 arc flash protective hood (10 cal/cm<sup>2</sup>, only with coverall)
- 1 protective coverall 8 or 11 cal/cm<sup>2</sup>, ASTM F1506 and NFPA 70E Standards or
- 1 arc flash protective jacket 11 cal/cm<sup>2</sup>, ASTM F1506 and NFPA 70E Standards
- 1 carrying bag for face shield and helmet
- 1 all kit carrying bag



<b>KIT-ARC-08-C*</b>	8 cal/cm <sup>2</sup> with coverall	Weight: 4.03 kg
<b>KIT-ARC-10-J*</b>	10 cal/cm <sup>2</sup> with jacket	Weight: 4.03 kg
<b>KIT-ARC-10-C*</b>	10 cal/cm <sup>2</sup> with coverall	Weight: 4.03 kg

\* Add size M, L or XL (S to 3XL on request).

### Arc flash protective kits

(25, 40, 55, 65 or 100 cal/cm<sup>2</sup>)

Composition of the kit:

- 1 arc flash protective hood with an integrated face shield 25, 40, 55, 65 or 100 cal/cm<sup>2</sup>, ASTM F2178 and NFPA 70E Standards
- 1 arc flash protective coat 25, 40, 55, 65 or 100 cal/cm<sup>2</sup>, ASTM F1506 and NFPA 70E Standards
- 1 arc flash protective bib overall 25, 40, 55, 65 or 100 cal/cm<sup>2</sup>, ASTM F1506 and NFPA 70E Standards
- 1 ABS helmet electrically insulated EN397, EN 50365, ANSI Z89.1 20kV.
- 1 safety glasses EN 166/EN 170
- 1 carrying bag for face shield and helmet
- 1 all kit carrying bag



**KIT-ARC-65/100**



**KIT-ARC-25**



**KIT-ARC-40/55**

<b>KIT-ARC-25-B*</b>	25 cal/cm <sup>2</sup> Indura Ultra Soft	Weight: 6.7 kg
<b>KIT-ARC-40-B*</b>	40 cal/cm <sup>2</sup> Indura Ultra Soft	Weight: 6.7 kg
<b>KIT-ARC-55-B*</b>	55 cal/cm <sup>2</sup> Indura Ultra Soft	Weight: 6.7 kg
<b>KIT-ARC-65-B*</b>	65 cal/cm <sup>2</sup> Kevlar/Nomex	Weight: 6.7 kg
<b>KIT-ARC-100-B*</b>	100 cal/cm <sup>2</sup> Kevlar/Nomex	Weight: 6.7 kg

\* Add size M, L or XL (S to 3XL on request).