





BMHC240ADWB

Solid Blocked Straight Connector
185-300 mm² Aluminium



BI con™

Application

Power cables with aluminium conductors.
Can be used with all jointing technologies:
cold shrink, heat shrink, resin etc.

Features


Profiled bores to enhance electrical contact and
increase mechanical constraint.
Full compliance with the **electrical** and **mechanical**
requirements of IEC 61238.



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
TEL 0044 191 490 1547 FAX 0044 477 5371
TEL 0044 117 977 4647 FAX 0044 977 5582
WWW.THORNEANDDERRICK.CO.UK



BMHC240ADWB Solid Blocked Straight Connector 185-300mm² Aluminium



Dimension Details

A	110 mm
B	35 mm
C	20 mm
D	20 mm

Technical Data

Connector Type	Solid Blocked Straight
Material Reference Number	8705001
Catalogue Number	BMHC240ADWB
Connector Material	Aluminium
Number of Conductor Bolts	2+2
AF	19 mm
Shear torque	35-40 Nm
Bolt Material	Brass
Central Connection Type	None
Central Connection Bolt	N/A
AF	N/A mm
Shear Torque	N/A Nm
Bolt Material	N/A
Connection Bolt Removable	N/A
AF	N/A mm
Conductor Cross Section Range	
Solid Aluminium	185-300 mm ²
Stranded Aluminium	185-240 mm ²
Stranded Copper	N/A mm ²
Stranded Flexible Copper	N/A mm ²
Overall Length	110 mm
Diameter	35 mm
Weight (each)	375 g
Shipping Quantity (min)	20 pieces
Test Standard	IEC 61238

*Technical Information subject to change without notice.

Accessories

BMHOLDER	Connector brace for use on installation
59020	Mastic filler kit (Pack of 6 Strips)
8702302	Brass Centralising Range Extension Sleeve for 50mm ² (Str Al/Cu) to 70mm ² (SAC Al/Cu)
8702304	Brass Centralising Range Extension Sleeve for 10mm ² (Str Al/Cu) tp 35mm ² (Str Al/Cu)



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
 TEL 0044 191 490 1547 FAX 0044 477 5371
 TEL 0044 117 977 4647 FAX 0044 977 5582
 WWW.THORNEANDDERRICK.CO.UK

