

Ball-Lok Ties



Quick and easy to apply, Ball-Lok ties offer a versatile and economical solution for most environments.

- BAND-IT Ball-Lok Ties installs with tools to ensure uniform tension and clean tail cut-off for safe handling. Its self locking design allows for fast installation and comes in two widths - 0.18" (4.6mm) and 0.31" (7.9mm)
- Available in Type 304 and Type 316 stainless steels to provide good to excellent corrosion resistance in a wide variety of environments
- Uncoated or coated with black, halogen free epoxy
- Loop tensile strengths range from 150 to 300 pounds

Ball-Lok Ties 304 and 316 Stainless Steel • Pack Qty – 100 (bag)


PART NUMBER 304 SS	PART NUMBER 316 SS	MAX BUNDLE DIAMETER		APPROXIMATE LENGTH		APPROXIMATE WIDTH		APPROXIMATE WEIGHT		MINIMUM LOOP TENSILE STRENGTH	
		IN	MM	IN	MM	IN	MM	LBS	KGS	LBS	N
KE1118	KE0118	1.2	30	5.9	150	0.18	4.6	0.42	0.19	200	890
KE1128	KE0128	2.0	50	7.9	201	0.18	4.6	0.57	0.26	200	890
KE1138	KE0138	2.7	69	10.2	259	0.18	4.6	0.70	0.32	200	890
KE1148	KE0148	4.0	102	14.2	360	0.18	4.6	0.92	0.42	200	890
KE1158	KE0158	6.0	152	20.4	520	0.18	4.6	1.32	0.60	200	890
KE1168	KE0168	8.0	203	26.8	679	0.18	4.6	1.76	0.80	200	890
KE1178	KE0178	10.0	254	33.0	838	0.18	4.6	2.07	0.94	200	890
KE1188	KE0188	12.0	305	42.0	1067	0.18	4.6	2.38	1.08	200	890
KE1328	KE0328	2.0	50	7.9	201	0.31	7.9	0.99	0.45	300	1335
KE1338	KE0338	2.7	69	10.2	259	0.31	7.9	1.32	0.60	300	1335
KE1348	KE0348	4.0	102	14.2	360	0.31	7.9	1.67	0.76	300	1335
KE1358	KE0358	6.0	152	20.4	520	0.31	7.9	2.23	1.04	300	1335
KE1368	KE0368	8.0	203	26.8	679	0.31	7.9	2.86	1.30	300	1335
KE1378	KE0378	10.0	254	33.0	838	0.31	7.9	3.52	1.60	300	1335
KE1388	KE0388	12.0	305	42.0	1067	0.31	7.9	4.62	2.10	300	1335
–	● KE0218	1.2	30	5.9	150	0.18	4.6	0.46	0.21	150	668
–	● KE0228	2.0	50	7.9	201	0.18	4.6	0.62	0.28	150	668
–	● KE0238	2.7	69	10.2	259	0.18	4.6	0.75	0.34	150	668
–	● KE0248	4.0	102	14.2	360	0.18	4.6	1.01	0.46	150	668
–	● KE0258	6.0	152	20.4	520	0.18	4.6	1.41	0.64	150	668
–	● KE0268	8.0	203	26.8	679	0.18	4.6	1.80	0.82	150	668
–	● KE0278	10.0	254	33.0	838	0.18	4.6	2.33	1.06	150	668
–	● KE0428	2.0	50	7.9	201	0.31	7.9	1.16	0.53	175	780
–	● KE0438	2.7	69	10.2	259	0.31	7.9	1.50	0.68	175	780
–	● KE0448	4.0	102	14.2	360	0.31	7.9	1.78	0.81	175	780
–	● KE0458	6.0	152	20.4	520	0.31	7.9	2.46	1.12	175	780
–	● KE0468	8.0	203	26.8	679	0.31	7.9	3.17	1.44	175	780
–	● KE0478	10.0	254	33.0	838	0.31	7.9	3.83	1.74	175	780

● COATED ○ UNCOATED



KE922 / K502 / or by hand

See pages 26-29 for full details on **TOOLS** and their specifications.



304 316

CE CE

