

Fully Coated Ball-Lok Ties

- Patent pending
- Fully Coated in Epoxy
- Improved strength
- Two widths and 5 lengths
- Halogen free
- 316 Stainless Steel
- Self locking for speedy application
- Smooth Internal Diameter
- Install by hand or with K502, KE922 tools



316 Stainless Steel

Package Quantity 100

Epoxy Coated



Cat. No.	Max.Bundle Diameter		Approximate Length		Approximate Width		Approximate Weight		Min. Loop Tensile Strength	
	<i>in</i>	<i>mm</i>	<i>in</i>	<i>mm</i>	<i>in</i>	<i>mm</i>	<i>Lbs.</i>	<i>Kg.</i>	<i>Lbs</i>	<i>N</i>
KE0228	2.0	50	7.9	201	0.18	4.6	0.62	0.28	150	668
KE0248	4.0	102	14.2	360	0.18	4.6	1.01	0.46	150	668
KE0258	6.0	152	20.4	520	0.18	4.6	1.41	0.64	150	668
KE0268	8.0	203	26.8	679	0.18	4.6	1.80	0.82	150	668
KE0278	10.0	254	33.0	838	0.18	4.6	2.33	1.06	150	668
KE0428	2.0	50	7.9	201	0.31	8.0	1.61	0.73	175	779
KE0448	4.0	102	14.2	360	0.31	8.0	1.85	0.84	175	779
KE0458	6.0	152	20.4	520	0.31	8.0	2.46	1.12	175	779
KE0468	8.0	203	26.8	679	0.31	8.0	3.17	1.44	175	779
KE0478	10.0	254	33.0	838	0.31	8.0	3.83	1.74	175	779



K502 Ball-Lok Tool with adjustable Tension and automatic cut off
Weight 0.94Lbs (0.43Kg)



KE922 Manual Tensioning Tool with tail cut-off lever
Weight 1.25Lbs (0.57Kg)



WWW.CABLEJOINTS.CO.UK
THORNE & DERRICK UK
 TEL 0044 191 490 1547 FAX 0044 477 5371
 TEL 0044 117 977 4647 FAX 0044 977 5582
 WWW.THORNEANDDERRICK.CO.UK



© Copyright BAND-IT - IDEX, INC.
 A Unit of IDEX Corporation
 Denver, Colorado U.S.A. 2001.
 All rights reserved.