

AC voltage detector for outdoor use

IEC 61243-1 edition 2*



IEC electronic voltage detector "Ultra Compact Series" for outdoor use.
 Ultimate "head capacitive technology" of voltage detector.
 Universal application 50/60Hz and wide band of voltage from 44 to 132kV.

Voltage presence is indicated by :

- **RED** flashind led (very bright, visible up to 20 m in direct lighting).
- powerful rated audible signal 67dB(A)/1.5 m.

Operating check :

- by pressing the Test Button, correct operation is indicated by red LED flashing on and a sound signal.
- After realeasing the Test Button, a timed green LED lights on.
- It indicates the good working order of the detector.

Contact electrodes (hook shaped) fitted to the body by screwing and easily interchangeable.

Delivered in a caring bag.
 For other voltage, please consult us.

CC-765-44/132



Contact electodes fitted to the housing by screwing and are easily interchangeable.

End fittings



CC-765-44/132-C

End fitting "C": hexagonal male 12 mm on flats, for hexagonal end fitting sticks.



CC-765-44/132-K

End fitting "K": for Universal end fitting sticks.



Reference	IEC 61243-1 edition 2	(Operating voltage)	Contact electrode	Case colour	type 6 LR 61	-25/+55 C°	350
CC-765-44/132	*	44 - 132 kV	Ø 120 mm		9 V		