

## Insulating stepladders

EN 131

Compact stepladders with insulating amounts reinforced polyester fiberglass with light alloy steps to work at height.  
Insulation between two steps: 30 000V  
Maximum load: 150 daN.  
Anti-pinch finger joints.

| Reference | Nbr steps | Height Access (m) | Height folded (m) | Height based feet (m) | kg  |
|-----------|-----------|-------------------|-------------------|-----------------------|-----|
| MP-700-4  | 3         | 2.58 m            | 1.39 m            | 0.68 m                | 5.9 |
| MP-700-1  | 4         | 2.81 m            | 1.64 m            | 0.91 m                | 6.9 |
| MP-700-2  | 5         | 3.04 m            | 1.89 m            | 1.14 m                | 8   |
| MP-700-3  | 6         | 3.27 m            | 2.14 m            | 1.37 m                | 9.4 |
| MP-700-5  | 7         | 3.50 m            | 2.39 m            | 1.60 m                | 11  |

### Optional accessories:

Replacement kit clogs slip MP 700-100.  
Replacement Kit toolholders MP 700-200.



MP-700-100



MP-700-200



## Folding stepladder with railing

Secure non-insulating platform.  
Maximum working load 150 daN.  
Rung footrest tested 260 daN.

| Reference | Nbr steps | Height Access | Height folded | Height based feet | kg   |
|-----------|-----------|---------------|---------------|-------------------|------|
| MP-700-6  | 4         | 2.93 m        | 1.48 m        | 0.93 m            | 19.5 |



**T&D** THORNE & DERRICK UK

Tel: +44 (0)191 490 1547  
Fax: +44 (0)191 477 5371  
Email: [northernsales@thorneandderrick.co.uk](mailto:northernsales@thorneandderrick.co.uk)  
Website: [www.cablejoints.co.uk](http://www.cablejoints.co.uk)  
[www.thorneandderrick.co.uk](http://www.thorneandderrick.co.uk)