



## Models for gate valves

Polyurethane. Easy to install with the two articulated parts\*. Padlock locking.  
 Prevents any handling of the gate valve.

| Reference | Holes<br>Ø<br>mm | Locks | Gate*<br>Ø<br>mm | Ext.<br>Ø<br>mm | Weight<br>g |
|-----------|------------------|-------|------------------|-----------------|-------------|
| HL-100    | 6                | 1     | 25 to 63,5       | 70              | 45          |
| HL-101    | 8                | 2     | 63,5 to 127      | 140             | 170         |
| HL-102    | 9                | 3     | 127 to 165       | 172             | 250         |
| HL-103    | 9                | 3     | 165 to 254       | 260             | 505         |
| HL-104    | 9                | 3     | 254 to 355       | 370             | 1055        |
| HL-105    | 9                | 1**   | 25 to 165        | -               | 225         |

\* Except HL-105, 2 parts.  
 \*\* 4 position settings.



Padlock locking.



HL-105

**POLYPROPYLENE  
 ADJUSTABLE MODEL**



## Models for 1/4 turn valves

Polyurethane. Easy to adjust with the two clip-in parts.  
 Padlock locking that prevents any quarter turn handling.

| Reference | Holes<br>Ø<br>mm | Locks        | Locking<br>mm | Dimensions<br>mm | Weight<br>g |
|-----------|------------------|--------------|---------------|------------------|-------------|
| HL-200    | 7                | 18 positions | 9.5 to 31.75  | 195              | 155         |
| HL-201    | 7                | 13 positions | 38.1 to 63.5  | 254              | 230         |
| HL-202    | 9                | 12 positions | 50.8 to 203.2 | 430              | 580         |



HL-200

8 adjustment positions.



HL-201

13 adjustment positions.



HL-202

12 adjustment positions.