





Head protection

Face shield

Protection against electric short-circuit arcs. Face shield adjustable on MO-182 helmet.
3-1,2 GW 1 SN DIN EN 166 8 1000 V.

| Reference | UV protection |  mm |  g |
|-----------|---------------|--|---|
| MO-184 | 100 % | 470 x 200 | 170 |



Caution: Do not use for welding operations.

Adjustable by rubber band.



Acetate face shield





EN 166 / EN 170
CE



Face shield on helmet MO-182/1-B.

ABS helmet

Safety industrial helmet. Standard sizes 53 to 63. Leather trim 21 cm along the inside for added comfort. Multiple adjustments for a perfect fit headband.

| Reference | Characteristics |  g |
|------------|--|---|
| MO-182/1-B | WHITE  | 300 |
| MO-182/1-R | RED  | 300 |
| MO-182/1-J | YELLOW  | 300 |




MO-182/1-R



MO-182/1-J

Deformable shock-resistant helmet with a "gutter" brim. Size from 53 to 62 cm. Lightweight with a comfort lining.

EN 397 440 V
EN 50365  1 000 V
ANSI Z89.1 20 000 V
CE



Safety chin strap




Side slots for mounting hearing protection.

Built-in cushion for optimum ventilation.

Multiple adjustments for a perfect fit headband: adjustable in 3 mm increments.

Polycarbonate helmet


Protects against vertical and side impacts, very well ventilated. Improved comfort. Adjustable size from 53 to 63 cm.

| Reference | Characteristics |  g |
|-----------|---|---|
| MO-183-BL | WHITE  | 455 |
| MO-183-RL | RED  | 455 |



MO-183-RL

Deformable shock-resistant helmet.

EN 12492
EN 397 440 V
EN 50365  1 000 V
ANSI Z89.1 20 000 V
CE

Head fit adjustment by milled wheel.

Chinstrap with an easy adjustment buckle. Designed to tear if hooked. (< 25 daN).

6-point cloth lining.



Dimensions



Weight