

Installation on bare conductors

IEC 61230



Reference	Rating (kA/1 s)	Installation on fixed points	Composition	Connection set
MT-5805	20	<ul style="list-style-type: none"> <li>• Ø 5-35</li> <li>— 16-40</li> <li>— 5-40</li> </ul>	3 clamps <b>MT-815-C</b> 1 <b>MT-840/1</b>	3 cables 95 mm <sup>2</sup> 1 earth cable 35 mm <sup>2</sup>
MT-8408	12,5	<ul style="list-style-type: none"> <li>• Ø 18-33</li> <li>—</li> <li>—</li> </ul>	3 clamps <b>MT-814/3</b> 1 <b>MT-840/1</b>	3 cables 70 mm <sup>2</sup> 1 earth cable 35 mm <sup>2</sup>
MT-9801	10	<ul style="list-style-type: none"> <li>• Ø 5-16</li> <li>— 0-16</li> <li>• Ø 5-28</li> </ul>	3 clamps <b>MT-817-C</b> 3 clamps <b>MT-814/2</b> 1 <b>MT-840/1</b>	3 cables 50 mm <sup>2</sup> 1 earth cable 25 mm <sup>2</sup>

Delivered in case.  
Clamp characteristics : see page 133.

Installation on permanent fixed points

Reference	Description
MT-890	Clamps 3 claws
MT-891	Earth clamp fixation
MT-893	Cable tensioner
MT-895	Cable kit support
CI-06-D	Wall mounted support

