



Low Voltage Heat Shrink Breakout Boots

Made from cross linked polyolefin and adhesive coated, these breakouts can be used in wide variety of applications. The sizes listed below are available from stock, other sizes available upon request.

Part Number	Legs	Skirt Dia (mm)		Leg Dia (mm)	
		Exp	Rec	Exp	Rec
2CB 30/12	2	30	12	14	4.5
2CB 40/16	2	40	16	15	5.0
2CB 60/23	2	60	23	25	7.5
3CB 38/17	3	38	17	14	4.5
3CB 60/25	3	60	25	25	8.0
3CB 80/38	3	80	38	35	11
3CB 110/50	3	110	50	46	18
3CB 125/57	3	125	57	55	20
4CB 40/15	4	40	15	14	3.5
4CB 65/26	4	65	26	26	7.0
4CB 82/37	4	82	37	30	9.0
4CB 100/47	4	100	47	38	12
4CB 125/52	4	125	52	52	15
5CB 80/33	5	80	33	26	8.0
5CB 100/42	5	100	42	34	10



Low Voltage Heat Shrink End Caps

- Adhesive lined to prevent water ingress
- Thick wall for extra strength and durability
- UV stable
- A range of live pot end kits available

Part Number	Cable Dia. (mm)	Expanded Dia. (mm)	Recovered Dia. (mm)
C12-4	4-7	12	4
C14-5	5-9	14	5
C25-8.5	9-20	25	8.5
C35-16	17-30	35	16
C40-15	16-35	40	15
C55-26	27-48	55	26
C75-36	37-65	75	36
C100-52	55-88	100	52
C120-60	65-105	120	60
C145-60	65-130	145	60
C160-82	85-145	160	82



Shrink Polymer Systems end caps are made from a semi-rigid cross linked polyethylene material which offers excellent weathering and abrasion resistance.

A full range of LV live pot end and abandonment kits are also available for most cable types, see page 49 for more details.