

# CABLE DRUM JACKS - RACK & PINION

## For heavy duty applications

Lifting capacity 1,500 to 10,000kg

An indispensable aid for cable laying

The jacks enable cable reels of a very large diameter to be lifted allowing the cable to be unreeled quickly and safely

Lifting on head or claw

Large base ensuring stability and safe operation

Wheel assemblies, allow easy movement of the jacks between jobs

The braked crank secures the load in any position

1.5 tonne jack has 3 claw positions allowing different sized reels to be raised

5 and 10 tonne jacks are supplied with a fixed head and adjustable claw. The claw is removable and can be located in 5 different height positions saving time in raising the jack to the required height

### Specifications

		0024015	0025011	0026018
Capacity on head	t	1.5	5.0	10.0
Capacity on claw	t	1.0	2.5	5.0
Lifting height	mm	265	410	500
Number of additional claws		2*	1**	1**
Weight without rollers	kg	30	69	105
Weight with rollers	kg	32	73	110
Position of	claw 1	200	341	520
	claw 2	380	453	632
	claw 3	558	565	744
	claw 4	-	677	856
	claw 5	-	789	968

### Dimensions

Lift ht. (mm)	265	410	495
A (mm)	300	700	700
B (mm)	500	400	400
C (mm)	623	1120	1180
D (mm)	558	1045	1100
E (mm)	-	853	1035
F (mm)	132	100	100
G (mm)	70	70	70
H (mm)	70	82	82
J (mm)	45	65	75
K (mm)	80	95	95
L (mm)	250	250	300
M (mm)	225	425	425
N (mm)	250	290	290
P (mm)	140	140	140
R (mm)	130	130	250

\* 1.5 with head and 2 fixed claws

\*\* claw with 5 adjustable positions



Suitable for the following drums

1.5T Jack 500 - 1600mmø

5.0T Jack 700 - 2820mmø

10.0T Jack 900 - 3200mmø