

## CABLE DRUM TRAILERS - Highway Range

CD60 Cable Drum Trailer



All of the Cable Trailers described below are equipped with braking and road lighting systems to conform with EEC Directives and are designed to travel fully laden at road speeds indicated on the UK Highway and most other European Countries. Variations can also be made to accommodate any individual Country specific requirements.

CD220 Cable Drum Trailer



For safe and easy drum handling, all SEB Cable Drum Trailers are fitted with hydraulic hand pump operated lift/lower systems as standard. When the drum is fully raised mechanical locks ensure drum security in transit. See separate page for details of additional options available.

(detailed specifications can be provided on request)

| Trailer Model | Payload (Approx.) | Gross Vehicle Weight | Max. Drum Width | Drum Dia. max/min | Spindle Dia. | Tow Eye/ Coupling Height Unladen | Trailer Width | Towing Speed | Tyres       | Brake System               |
|---------------|-------------------|----------------------|-----------------|-------------------|--------------|----------------------------------|---------------|--------------|-------------|----------------------------|
| SINGLE AXLE   |                   |                      |                 |                   |              |                                  |               |              |             |                            |
| CD20          | 795Kg             | 1095Kg               | 1075mm          | 1200/650          | 50mm         | 50/630                           | 1900          | 100Kmh       | 165x13      | Overrun Auto reverse       |
| CD32          | 1200Kg            | 1600Kg               | 1375mm          | 2100/700          | 50mm         | 50/620                           | 2280          | 100Kmh       | 175x14      | Overrun Auto reverse       |
| CD40          | 1500Kg            | 2000Kg               | 1250mm          | 2200/750          | 50mm         | 50/630                           | 2200          | 100Kmh       | 195x14      | Overrun Auto reverse       |
| CD60          | 2350Kg            | 3100Kg               | 1280mm          | 2500/1060         | 76mm         | 50/610                           | 2300          | 100Kmh       | 215/75R17.5 | Overrun Auto reverse       |
| CD70          | 2750Kg            | 3500Kg               | 1280mm          | 2500/1060         | 76mm         | 50/610                           | 2300          | 100Kmh       | 215/75R17.5 | Overrun Auto reverse       |
| PT60          | 2300Kg            | 3100Kg               | 1710mm          | 3200/1420         | 76mm         | 50/680                           | 2495          | 100Kmh       | 215/75R17.5 | Overrun Auto reverse       |
| PT 70         | 2750Kg            | 3500Kg               | 1600mm          | 3200/1420         | 76mm         | 50/680                           | 2545          | 100Kmh       | 215/75R17.5 | Overrun Auto reverse       |
| CD130         | 5200Kg            | 6580Kg               | 1470mm          | 2860/1360         | 76mm         | 76/710                           | 2550          | 100Kmh       | 11.00x22.5  | 2 Line Air / Mech. C/W ABS |
| CD140         | 5050Kg            | 6650Kg               | 1600mm          | 3200/2000         | 89mm         | 76/810                           | 2550          | 100Kmh       | 11.00x22.5  | 2 Line Air / Mech. C/W ABS |
| TWIN AXLE     |                   |                      |                 |                   |              |                                  |               |              |             |                            |
| CD220         | 8550Kg            | 10650Kg              | 1730mm          | 3660/2550         | 101mm        | 76/780                           | 2550          | 100Kmh       | 235/75R17.5 | 2 Line Air / Mech. C/W ABS |

NOTE:

1) All Drum widths stated are with drum locking collars fitted to spindles.

2) These trailers constitute our standard/popular range. However if there is not a trailer listed to accommodate your drum size and weight then please do not hesitate to contact us.