

14.4 V CORDLESS HYDRAULIC CRIMPING TOOL



B 131-C

general features

Crimping force kN	Dimensions mm			Battery	Weight kg (with battery)
	length	height	width		
130	420	250	100	14,4 V 3.0 Ah	7,4



- 14.4 V cordless hydraulic crimping tool, lightweight and balanced for single hand operation. This tool will accept all semi-circular slotted dies, common to most 130 kN tools.
- The tool features a double speed action: a fast advancing speed for rapid approach of the dies to the connector and a slower more powerful speed for crimping.
- For ease of operation and comfort of the operator the tool head can be fully rotated through 180 degrees.
- The tool is powered by 14.4 V dc Ni-MH battery.
- A balanced tool for optimum control.
- Quiet in operation with very little vibration.
- Lightweight construction enables the operator to hold the tool in

one hand and to position the connector with the other hand.

- The operating buttons, crimp/release, are mechanically interlocked, to prevent accidental operation of the tool.
- A microprocessor controls the tool operation and automatically cuts out the motor, on completion of the crimping operation, saving energy and extending battery life.

MAIN APPLICATIONS - max section mm ²			
L.V. lugs and splices	Insulated terminals	"C" sleeve Connectors	H.V. lugs and splices
400	240	185	400

STORAGE				
Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
VAL P19	542x412xh197	3,2	*	—

Available upon request:

- ESC600 cable for connection to a 12V dc external power supply/vehicle battery length 6 m.

The tool is supplied with:

- Basic tool complete with battery and shoulder strap
- Spare battery
- Battery charger
- Plastic carrying case suitable for storing 14 sets of semi-circular slotted dies



B 131-C-KV
plastic coated version



Also available in the B 135 version with vertical handle.



B 131L-C

general features



Crimping force kN	Dimensions mm			Battery	Weight kg (with battery)
	length	height	width		
130	460	250	100	14,4 V 3.0 Ah	8,2



MAIN APPLICATIONS - max section mm ²			
L.V. lugs and splices	Insulated terminals	"C" sleeve Connectors	H.V. lugs and splices
400	240	185	400

STORAGE				
Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
VAL P19	542x412xh197	3,2	*	—

Also available in the "B131L-C" version, featuring a large 42 mm jaw opening, for an easier introduction/removal of large size compression terminations and joints.



These tools are supplied without dies. For die selection, please refer to chart on pages 124 to 128