



## RF-M



### Technical characteristics

Easy entry	yes
Min operating temperature range	-4 °F
Max operating temperature range	176 °F
Max operating temperature range (surge)	194 °F
Dimensional form	Ring terminal
Material (Body)	Electrolytic copper
Material (Partially reinforced)	PVC

### Media gallery













### Attachments




DATASHEET








### List of products



	Type	Color	Ø	B	M	N	L	d	Pack qty	Min. pack qty	
	RVF-R4	Red	0.15 in.	0.22 in.	0.18 in.	0.11 in.	0.69 in.	0.13 in.	3,000	100	
	RVF-R6	Red	0.15 in.	0.22 in.	0.18 in.	0.11 in.	0.69 in.	0.15 in.	3,000	100	
	RVF-R8	Red	0.15 in.	0.28 in.	0.26 in.	0.14 in.	0.79 in.	0.17 in.	3,000	100	
	RVF-R10	Red	0.15 in.	0.31 in.	0.28 in.	0.15 in.	0.83 in.	0.21 in.	3,000	100	
	RVF-R14	Red	0.15 in.	0.37 in.	0.32 in.	0.19 in.	0.9 in.	0.25 in.	3,000	100	
	RVF-R516	Red	0.15 in.	0.47 in.	0.41 in.	0.24 in.	1.04 in.	0.33 in.	2,000	100	
	RVF-R38	Red	0.15 in.	0.61 in.	0.51 in.	0.3 in.	1.22 in.	0.41 in.	1,500	100	
	RVF-R12	Red	0.15 in.	0.71 in.	0.61 in.	0.35 in.	1.36 in.	0.51 in.	1,500	100	

**RF-M** Cable type: copper, Minimum section: 22 AWG, Maximum section: 16 AWG



	Type	Color	Ø	B	M	N	L	d	Pack qty	Min. pack qty	
	RVF-R4	Red	0.15 in.	0.22 in.	0.18 in.	0.11 in.	0.69 in.	0.13 in.	3,000	100	
	RVF-R6	Red	0.15 in.	0.22 in.	0.18 in.	0.11 in.	0.69 in.	0.15 in.	3,000	100	
	RVF-R8	Red	0.15 in.	0.28 in.	0.26 in.	0.14 in.	0.79 in.	0.17 in.	3,000	100	
	RVF-R10	Red	0.15 in.	0.31 in.	0.28 in.	0.15 in.	0.83 in.	0.21 in.	3,000	100	
	RVF-R14	Red	0.15 in.	0.37 in.	0.32 in.	0.19 in.	0.9 in.	0.25 in.	3,000	100	
	RVF-R516	Red	0.15 in.	0.47 in.	0.41 in.	0.24 in.	1.04 in.	0.33 in.	2,000	100	

	<a href="#">RVF-R38</a>	Red	0.15 in.	0.61 in.	0.51 in.	0.3 in.	1.22 in.	0.41 in.	1,500	100	
	<a href="#">RVF-R12</a>	Red	0.15 in.	0.71 in.	0.61 in.	0.35 in.	1.36 in.	0.51 in.	1,500	100	