




HEAVY DUTY COPPER TUBE TERMINALS

2A-M



Conductor Size sqmm	Ø Stud mm	Ref.	Dimensions mm						Quantity Box/Bag	Mechanical Tools		Hydraulic Tools										
			Øi	B	M	N	L	d		HN 5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520
16	8	2 A 3-M 8	5,8	15,0	9	8	43,5	8,4	600/100	HN 5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520
	10	2 A 3-M 10	5,8	18,0	11	10	47,5	10,5	500/100													
25	8	2 A 5-M 8	7,0	15,0	9	8	51,0	8,4	400/100	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	10	2 A 5-M 10	7,0	18,0	11	10	55,0	10,5	300/50													
35	12	2 A 5-M 12	7,0	21,0	14	12	60,0	13,2	300/50	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	8	2 A 7-M 8	8,9	17,0	9	8	53,0	8,4	250/50													
50	10	2 A 7-M 10	8,9	19,0	11	10	57,0	10,5	250/50	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 7-M 12	8,9	21,0	14	12	62,0	13,2	250/50													
63	10	2 A 10-M 10	10,0	20,0	11	10	63,0	10,5	200/50	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 10-M 12	10,0	21,0	14	12	68,0	13,2	150/50													
70	14	2 A 10-M 14	10,0	25,0	16	14	72,0	15,0	150/50	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 10-M 16	10,0	26,0	18	16	76,0	17,0	150/50													
95	10	2 A 14-M 10	11,3	21,0	11	10	70,0	10,5	100/50	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 14-M 12	11,3	22,0	14	12	75,0	13,2	100/50													
120	14	2 A 14-M 14	11,3	25,0	16	14	79,0	15,0	100/50	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 14-M 16	11,3	26,0	18	16	83,0	17,0	100/50													
125	10	2 A 19-M 10	13,5	25,0	11	10	76,5	10,5	75/25	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 19-M 12	13,5	25,0	14	12	81,5	13,2	75/25													
150	14	2 A 19-M 14	13,5	25,0	16	14	85,5	15,0	75/25	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 19-M 16	13,5	27,0	18	16	90,5	17,0	75/25													
185	20	2 A 19-M 20	13,5	29,5	22	20	97,5	21,0	75/25	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	10	2 A 24-M 10	15,2	28,5	11	10	82,0	10,5	50/25													
240	12	2 A 24-M 12	15,2	28,5	14	12	87,0	13,2	50/25	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	14	2 A 24-M 14	15,2	28,5	16	14	91,0	15,0	50/25													
300	16	2 A 24-M 16	15,2	28,5	18	16	95,0	17,0	50/25	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	20	2 A 24-M 20	15,2	30,0	22	20	103,0	21,0	50/25													
300	10	2 A 30-M 10	16,7	31,5	13	11	92,0	10,5	50/25	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 30-M 12	16,7	31,5	16	14	98,0	13,2	30/15													
400	14	2 A 30-M 14	16,7	31,5	18	16	102,0	15,0	30/15	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 30-M 16	16,7	31,5	19	17	104,0	17,0	30/15													
400	20	2 A 30-M 20	16,7	31,5	22	20	110,0	21,0	30/15	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 37-M 12	19,2	35,5	16	14	108,0	13,2	30/15													
400	14	2 A 37-M 14	19,2	35,5	18	16	112,0	15,0	30/15	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 37-M 16	19,2	35,5	19	17	114,0	17,0	30/15													
500	20	2 A 37-M 20	19,2	35,5	22	20	120,0	21,0	30/15	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 48-M 12	21,1	39,0	16	14	109,0	13,2	20/5													
500	14	2 A 48-M 14	21,1	39,0	18	16	113,0	15,0	20/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 48-M 16	21,1	39,0	19	17	115,0	17,0	20/5													
600-630	20	2 A 48-M 20	21,1	39,0	22	20	121,0	21,0	25/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 60-M 12	23,7	44,0	20	14	129,5	13,2	20/5													
600-630	14	2 A 60-M 14	23,7	44,0	22	16	133,5	15,0	20/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 60-M 16	23,7	44,0	22	19	136,5	17,0	20/5													
800	20	2 A 60-M 20	23,7	44,0	24	23	142,5	21,0	20/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	12	2 A 80-M 12	27,0	51,0	22	19	140,0	13,2	15/5													
800	14	2 A 80-M 14	27,0	51,0	22	19	140,0	15,0	10/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 80-M 16	27,0	51,0	22	19	140,0	17,0	10/5													
1000	20	2 A 80-M 20	27,0	51,0	24	23	146,0	21,0	15/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 100-M 16	30,3	56,5	22	19	147,0	17,0	10/5													
1000	20	2 A 100-M 20	30,3	56,5	24	23	153,0	21,0	10/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	16	2 A 120-M 16	33,4	61,5	22	19	159,0	17,0	20/5													
1000	20	2 A 120-M 20	33,4	61,5	24	23	165,0	21,0	20/5	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	
	20	2 A 160-M 20	38,0	72,0	24	23	187,0	21,0	12/3													
1000	20	2 A 200-M 20	44,0	80,0	24	23	202,0	21,0	6/2	TN 70 SE	TN 120 SE	HT 45-E	HT 51	RH 50	B 51	B 55	HT 81-U	RHU 81	HT 120 and tools and heads with 130 kN crimping force	ECW-H3D	RHU 520	

2A-M series are made from high purity copper tube, and are annealed. They feature a double length barrel for enhanced electrical and mechanical performance in heavy duty applications.

The absence of an inspection hole prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.

The terminals are electrolytically tin plated to prevent atmospheric corrosion. 2A-2M series terminals with double stud hole palm are available against specific requirements.

