## HYDRAULIC CUTTING TOOL

## general features

Mex cutting Ø - mm	Dimens	- Weight	
	length	with	kj
85	<b>652,5</b>	175	8,6

Ì	BTORAGE					
	Тура	Dimensions mm	Weight kg	Supplied with the tool	Aveileble upon request	
ľ	VAL P7	727x202xh115	1.3	*	_	



HT-TC0851

The tool features a double speed action: a fast advancing speed for rapid approach of the blades to the cable and a slower more powerful speed for cutting.

The blades are manufactured from high strength special steel, heat treated to ensure a long service life.

The head can easily be opened to allow the cutting of running cables, and can rotate through 180 degrees, to enable the operator to work in the most comfortable position.

HT-TC0851 features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.

## **HYDRAULIC CUTTING HEAD**



general features

Max cutting Ø mm	Max operating pressure — ber	Dimensions mm		Weight
		bogth	with	Weight Kg
85	700	409	135	4,9

BTORAGE					
Тура	Dimensions mm	Weight kg	Supplied with the tool	Aveileble upon request	
VALTO DRS	485v455vb85	2.4		_	



TC 085

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 136-138)

TCO85 features the same cutting capability as HT-TCO851.