

## INDUSTRIAL APPLICATION HT-TC051

Hand operated hydraulic tool specifically designed to cut copper, aluminium and telecommunications cables having a max overall diameter of 50 mm.

The tool features a double speed action: a fast advancing speed for rapid approach of the blades to the cable and a slower more powerful speed for cutting.

The blades are manufactured from high strength special steel, heat treated to ensure a long service life.

The head can be easily opened to allow the cutting of running cables. The head can rotate through 90 degrees, to enable the operator to work in the most comfortable position. HT-TC051 features an automatic

## HYDRAULIC CUTTING TOOL

### general features

Max cutting Ø mm	Dimensions mm		Weight kg
	length	width	
50	497	129	4,38

#### STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
Canvas Bag Ø10	545x160	0,15	*	—

safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.



## INDUSTRIAL APPLICATION TC 050

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max. (see page 136-138)

TC050 features the same cutting capability as HT-TC051.

## HYDRAULIC CUTTING HEAD

### general features



Max cutting Ø mm	Max operating pressure bar	Dimensions mm		Weight kg
		length	width	
50	700	325	112	3,2

#### STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
Canvas bag Ø11	360x137	0,13	*	—



## INDUSTRIAL APPLICATION HT-TC065

Hand operated hydraulic tool specifically designed to cut copper, aluminium and telecommunications cables having a max overall diameter of 65 mm.

The tool features a double speed action.

The blades are manufactured from high strength special steel, heat treated to ensure a long service life.

The head can be easily opened to allow the cutting of running cables.

The head can rotate through 320 degrees, to enable the operator to work in the most comfortable position. HT-TC065 features an automatic safety valve to bypass oil when reach-

## HYDRAULIC CUTTING TOOL

### general features

Max cutting Ø mm	Dimensions mm		Weight kg
	length	width	
65	523	129	5,3

#### STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
Canvas bag Ø10	545x160	0,15	*	—

ing maximum pressure; a pressure release device can also be operated at any stage of operation.



**New**