

Ex Instruments Catalogue Spring 2012



Contents

5	
ToughPIX 2301XP ToughPIX 2302XP ToughPIX 2303XP ToughPIX 2304XP	p4 p5 p6 p7
Ultrasonic Thickness Gauges	
UT5000	p8
Laser Distance Meters	
LaserMETER 3000XP	p10
Accessories	
XP Series Battery Pack XP Series Replacement Fuse Kit XP Series Power Supply XP Series Battery Fixing Kit XP Series Charging Station XP Series Leather Harness XP Series Replacement USB Plug XP Series USB Communication Wand XP Series Optical accessory kit XP Series Leather Holster Ultrasonic Couplant Gel ATEX Certified RFID Tags Spare Dual Element Transducer Refresh Kit	p11 p12 p12 p13 p13 p14 p14 p14 p15 p15 p16 p16 p17 p17
Software	

Software

CorDEX CONNECT [™] Predictive Maintenance System	p18
CAMS CorDEX Asset Management Software	p18

» Online training

» Where to buy

Contact Info

Find your International contact

More CorDEX Info Online

- » Latest products
- » Application guides
- » Firmware updates

www.cordexinstruments.com

United Kingdom



WWW.CABLEJOINTS.CO.UK THORNE & DERRICK UK TEL 0044 191 490 1547 FAX 0044 477 5371 TEL 0044 117 977 4647 FAX 0044 977 5582 WWW.THORNEANDDERRICK.CO.UK

United States General product & sales information

Tel: 1-877-836-0764 Email: us.sales@cord-ex.com

Protection Key

Use these icons to identify the protection concepts used in your instrument.



Instrinsically safe device, power controlled to prevent sparks.



p19

Flameproof device, gas expansion controlled to prevent explosions.



Encapsulated device sparks controlled by removing gas/ oxygen using compound.

About Us



Spring 2012

CorDEX Instruments Ltd, an ISO 9001:2008 certified manufacturer of high quality hand-held inspection & NDT devices for use within hazardous (potentially explosive) environments.

With in-house design capability, all products are manufactured in line with a BS EN13980:2002 registered manufacturing system, ensuring the utmost quality and repeatability.

Our ever expanding global distribution network along with continual investment in research & development of new, innovative safety products ensures CorDEX Instruments are positioned to become the premier manufacturer of hand-held explosive area equipment and accessories.



Education & Training



CorDEX Instruments is focused on the advancement in education services to the Oil & Gas, Manufacturing, Engineering and petrochemical industries.

Through educational programmes and support, CorDEX Instruments are helping to enhance both individual and company workplace understanding of the hazardous areas in which they work and provide them will the knowledge of products that will help to keep them safe.

Training

- Specific Features <u>MultiPCHO</u>^{ex}Techt • <u>MultiPCHO^{ex}</u> is wire table DROFF wires UT 2000 fireways • UTS900 examples of the target incodes, mercing any pactors reading and becetting actual reading • UTS900 examples for accepted reading addressing providing
 - reading esta

CorDEX Instruments will be setting up a new online training centre where you can learn about hazardous areas, products and their roles and the technology behind them.

With a 'Self-paced' tutorial structure it allows you to learn and watch the tutorials, when it suits you.

Look out for the New 'Training' section on the CorDEX Instruments Website.

Follow Us...





For the latest products, news, videos and applications, or if you just want to know where we are and what we are doing, check us out on any of the above.

ToughPIX 2301XP Digital Camera



ATEX Certified for Zone 1, IIC T4 areas



For Class I, Div.1 Certified versions of ToughPIX digital camera see page **7**.

Specifications	
ATEX Certificate No:	Sira 08ATEX1293X
ATEX Certificate Type:	0518 II 2 G / Ex d IIC T4 Gb
Ambient Temperature:	Tamb -20C to +50C
Image download	High Speed USB (safe area only)
Memory capacity	4GB
Standard image capture resolution	5 Megapixel
Zoom	Up to 6x zoom
Screen size	2.4 inches
Additional Features	Red-eye reduction
Tripod mount	1/4 inch 20 TPI
Body Material	Anodised aluminium with anti-static over mould
Lens & LCD Material	Armoured Glass
Weight	1.5kg
IP	54
Battery type	Removable & Rechargeable
Capacity	1100mAh
Cell type	NiMH

Description

The **ToughPIX 2301XP** explosion proof digital camera enables documentation of equipment and processes within potentially explosive areas quickly and easily, its large easy access controls also allow operation when wearing protective clothing. The ToughPIX 2301XP incorporates an onboard, fully automatic strobe flash for image capture in extreme, low light situations. These still and moving images can be easily reviewed within the hazardous area on the armoured LCD screen.

Features

The ToughPIX 2301XP is packed with the following features;

- » ATEX Certified for use in Zone 1 IIC T4 hazardous areas.
- » Tough, industrial grade design.
- » Full strobe flash for low light work.
- » Removable/Rechargeable battery pack.
- » 6x digital zoom.
- » 4GB of onboard memory.
- » CAMS asset management & reporting software.

Supplied with

- » Hard Carry Case
- » Battery Pack
- » Battery Removal Tool
- » USB Communication Wand
- » Power Supply
- » Charging Station
- » Wrist Strap
- » 2 x Spare Fuses
- » CAMS Software Licence
- » Documentation CD

For more information visit www.cordexinstruments.com

ToughPIX 2302XP Digital Camera



ATEX Certified for mining (M2) applications



For Class I, Div.1 Certified versions of ToughPIX digital camera see page **7**.

Specifications	
ATEX Certificate No:	Sira 08ATEX1293X
ATEX Certificate Type:	0518 l M2 / Ex d l Mb
Ambient Temperature:	Tamb -20C to +50C
Image download	High Speed USB (safe area only)
Memory capacity	4GB
Standard image capture resolution	5 Megapixel
Zoom	Up to 6x zoom
Screen size	2.4 inches
Additional Features	Red-eye reduction
Tripod mount	1/4 inch 20 TPI
Body Material	Anodised aluminium with anti-static over mould
Lens & LCD Material	Armoured Glass
Weight	1.5kg
IP	54
Battery type	Removable & Rechargeable
Capacity	1100mAh
Cell type	NiMH

Description

The ToughPIX 2302XP explosion proof digital camera is the ultimate tool for mining professionals, allowing documentation of equipment and processes within a mining environment, its large access controls also allow operation when wearing protective clothing. The ToughPIX 2302XP incorporates an onboard, fully automatic strobe flash for image capture in extreme, low light situations. These captured images can be viewed for clarity and content quickly and easily in the hazardous area on the armoured LCD screen.

Features

The ToughPIX 2302XP is packed with the following features;

- » ATEX Certified for use in I M2 / Ex d I Mb hazardous areas.
- » Tough, industrial grade design.
- » Full strobe flash for low light work.
- » Removable/Rechargeable battery pack.
- » 6x digital zoom.
- » 4GB of onboard memory.
- » CAMS asset management & reporting software.

- » Hard Carry Case
- » Battery Pack
- » Battery Removal Tool
- » USB Communication Wand
- » Power Supply
- » Charging Station
- » Wrist Strap
- » 2 x Spare Fuses
- » CAMS Software Licence
- » Documentation CD

ToughPIX 2303XP Digital Camera



ATEX Certified for gas & mining applications



For Class I, Div.1 Certified versions of ToughPIX digital camera see page **7**.

Specifications

ATEX Certificate No:Sira 08ATEX1293XATEX Certificate Type:0518 I/II 2/M2 G / Ex d I Mb Ex d IIC T4 GbAmbient Temperature:Tamb -20C to +50CImage downloadHigh Speed USB (safe area only)Memory capacity8GBStandard image capture resolution5 MegapixelZoomUp to 6x zoomScreen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialArmoured GlassLens & LCD Material37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacityNiMH	specifications	
Ambient Temperature:Tamb -20C to +50CImage downloadHigh Speed USB (safe area only)Memory capacity8GBStandard image capture resolution5 MegapixelZoomUp to 6x zoomScreen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	ATEX Certificate No:	Sira 08ATEX1293X
Image downloadHigh Speed USB (safe area only)Memory capacity8GBStandard image capture resolution5 MegapixelZoomUp to 6x zoomScreen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	ATEX Certificate Type:	0518 I/II 2/M2 G / Ex d I Mb Ex d IIC T4 Gb
Memory capacity8GBStandard image capture resolution5 MegapixelZoomUp to 6x zoomZoomUp to 6x zoomScreen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Ambient Temperature:	Tamb -20C to +50C
Standard image capture resolution5 MegapixelZoomUp to 6x zoomZoomUp to 6x zoomScreen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Image download	High Speed USB (safe area only)
capture resolutionUp to 6x zoomZoomUp to 6x zoomScreen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Memory capacity	8GB
Screen size2.4 inchesAdditional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh		5 Megapixel
Additional FeaturesRed-eye reductionTripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Zoom	Up to 6x zoom
Tripod mount1/4 inch 20 TPIBody MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Screen size	2.4 inches
Body MaterialAnodised aluminium with anti-static over mouldLens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Additional Features	Red-eye reduction
Lens & LCD MaterialArmoured GlassLens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Tripod mount	1/4 inch 20 TPI
Lens kit37mm combination macro 0.45 wide angle lens AFWeight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Body Material	Anodised aluminium with anti-static over mould
Weight1.5kgIP54Battery typeRemovable & RechargeableCapacity1100mAh	Lens & LCD Material	Armoured Glass
IP 54 Battery type Removable & Rechargeable Capacity 1100mAh	Lens kit	37mm combination macro 0.45 wide angle lens AF
Battery type Removable & Rechargeable Capacity 1100mAh	Weight	1.5kg
Capacity 1100mAh	IP	54
	Battery type	Removable & Rechargeable
Cell type NiMH	Capacity	1100mAh
	Cell type	NiMH

Description

The **ToughPIX 2303XP** explosion proof digital camera is designed with the professional inspector in mind. Certified for use in hazardous areas both above and below ground, the ToughPIX 2303XP is also supplied with macro & wide angle lens for close up and wide area photography. With the addition of the removable low intensity LED lamp makes this the ultimate image capturing tool for hazardous areas.

Features

The ToughPIX 2303XP is packed with the following features;

- » ATEX Certified for use above & below ground hazardous areas.
- » Tough, industrial grade design.
- » Macro facility for close up imagery.
- » Removable/Rechargeable battery pack.
- » 6x digital zoom.
- » 8GB of onboard memory.
- » CAMS asset management & reporting software.

Supplied with

- » Hard Carry Case
- » Battery Pack
- » Battery Removal Tool
- » USB Communication Wand
- » Power Supply
- » Charging Station
- » Wrist Strap
- » 2 x Spare Fuses
- » CAMS Software Licence
- » Optical Accessory Kit
- » Documentation CD

For more information visit www.cordexinstruments.com

ToughPIX 2304XP Digital Camera



CSA Certified - Explosion proof Digital Camera





For ATEX Certifed versions of ToughPIX digital camera see pages **4 through 6**.

Specifications

specifications	
CSA Certificate No	Class I Div 1 B,C,D (CSA)
CSA Certificate Type	Class I, Div.1, Groups B, C & D
Ambient Temperature	Tamb -4° F to +122° F
Image download	High Speed USB (safe area only)
Image storage	4GB or 8GB
Standard image capture resolution	5 Megapixel
Zoom	Up to 6x Zoom
Screen size	2.4 inches
Additional Features	Red-eye reduction
Tripod mount	1/4 inch 20 TPI
Body Material	Anodised aluminium with anti-static over mould
Lens & LCD Material	Armoured Glass
Weight	3.3lbs
Ingress Protection	NEMA 3R
Battery type	Removable & Rechargeable
Capacity	1100mAh
Cell type	NiMH



Download the **Weatherford Case Study** to read more about how the ToughPIX 2300XP Series can be used in hazardous areas.

Download here: www.cordexinstruments.com/TGH6

Description

The **ToughPIX 2304XP** explosion proof handheld digital camera is the ultimate tool for digital photography and is designated Class I Div 1 hazardous (explosive) areas. Incorporating features usually found in high end digital SLR cameras, the ToughPIX 2304XP provides petrochemical professionals with the ability to take high quality still and moving images of plant quickly and safely.

Features

A fully featured handheld digital camera, the ToughPIX 2304XP is supplied as standard with the following;

- » CSA Certified for use in Class I Div 1 hazardous areas.
- » Interchangeable standard, macro and wide angle lenses.
- » Upto 8GB onboard memory.
- » Full colour LCD display.
- » Flash and lamp for low light work.
- » CAMS database reporting software.

- » Hard Carry Case
- » Battery Pack
- » Battery Removal Tool
- » USB Communication Wand
- » Power Supply
- » Charging Station
- » Wrist Strap
- » 2 x Spare Fuses
- » CAMS Software Licence
- » Optical Accessory Kit (8GB only)
- » Documentation CD

UT5000



ATEX and IECEx Certified – Intrinically Safe Thickness Gauge





Specifications

specifications	
ATEX Certificate No:	Baseefa11ATEX0114
IECEx Certificate No:	IECEx BAS 11.0094
ATEX/IECEx Certificate Type:	II 2 G Ex ib IIC T4 Gb
Memory	Stores up to 1000 measurements
Screen	8cm (3.1inch) RGB TFT colour screen with backlight Right/left handed set up
Material Velocity Selection	Preloaded via Drop-Down menu, or user defined
Transducer	Dual Element
Pulse Rate	Standard transmit pulse rate of 4Hz Adjustable from single shot up to 8Hz
Receiver Bandwidth	1MHz to 15MHz (-3dB points)
Frequency	4MHz, 3mm up to 100mm (0.02in to 3.9in)
Accuracy	+/- 0.05mm (0.002in)
RFID Tag Reader	 » Operates with 13.54MHz passive tags » Detection range up to 5cm (1.9in) » SupportsISO/IEC15693-2,ISO/IEC18000-3 tag formats
Battery Details	 » Lithium thionyl chloride primary 3.6V cell » 100 hours continuous operation with back light restrictions low battery warning
Operating Temperature	-10 to +50C (14°F to 122°F)
Weight	1Kg (2.2lb)

Description

The UT5000 Intrinsically Safe thickness gauge with CorDEX CONNECT[™] measures material thickness for Non-Destructive Testing (NDT) and Predictive Maintenance (Pdm) on pipelines, storage tanks and fixed equipment within hazardous locations.

Features

- » Troubleshoot problems immediately with no hot work permit required.
- » ATEX & IECEx Certified Zone 1 IIC T4.
- » Built in RFID tag reader, link your measurements to the location.
- » All parameters at a glance with the backlit, full colour LCD screen.
- » Continuous measurement mode to highlight corrosion and thinning.
- » MultiECHO[™] technology to eliminate irregular echoes.
- » Displays measurements in Imperial or Metric units.
- » CorDEX CONNECT predictive maintenance system supplied as standard.
- » Pre-loaded material velocity table.

- » Hard Carry Case
- » 1 x Dual Element Transducer
- » USB Communication Wand
- » 1 x Couplant Gel
- » Battery Pack
- » 2 x Wrist Strap
- » 5 x ATEX RFID Tags
- » CorDEX CONNECT ™Licence
- » Documentation CD

UT5000



ATEX and IECEx Certified – Intrinically Safe Thickness Gauge



LaserMETER 3000XP



ATEX, IECEx & CSA Certified -Explosion proof laser distance meter





Specifications

Specifications	
ATEX Certificate No:	Sira 10ATEX1283X
IECEx Certificate No:	IECEx SIR 10.0133X
ATEX/IECEx Certificate Type:	I/II M2/2 G Ex d I/IIC T4
CSA Certificate No:	2379424
CSA Certificate Type:	Class I Div.1 Groups B, C, D
Ambient Temperature:	Tamb -20C to +50C (-4F to + 122F)
Range	0.5m to 30m (1.6ft to 118ft)
Measuring Accuracy	Typically: 3mm (0.01in)
Measurement Unit Displayed	1mm (0.03in)
Laser Type/ Class	635mm, <1 mW, II
Acc	IEC 60825-1 : 2001
Body/ Lens and LCD	Cast Aluminium chassis with anti-static over mould/ Toughened Safety Glass
Emitted Wavelength	620-690nm
IP	65
Weight	<1kg (<2.2lbs)
Dimensions	140L x 130H x 75W mm (5.5 x 5.1 x 2.9 in)
Functions	Pythagoras, Volume, Area
Battery type	Rechargeable
Capacity	1100mAh
Cell type	NiMH

Description

LaserMETER 3000XP explosion proof laser distance meter designed for use in hazardous (explosive) areas. With its rugged IP65 design, and on-board mathematics it is the ultimate hazardous area distance measurement tool.

The LaserMETER 3000XP can offer you speed, accuracy, safety, versatility, convenience and functionality in comparison to traditional measuring methods.

Features

- » ATEX & IECEx Certified I/IIM2/2 G Ex d I/IIC T4.
- » CSA Certified Class I, Div.1 B,C,D.
- » Use in all conditions with a clear backlit LCD screen.
- » Single or continuous measurement.
- » Pythagoras, area and volume calculations.
- » Interchangeable/rechargeable battery.
- » Displays measurements in Imperial or Metric units.

- » Battery Pack
- » Battery Removal Tool
- » Power Supply
- » Charging Station
- » Wrist Strap
- » Documentation CD



XP Series Battery Pack



Description

The CorDEX Instruments **XP Series Battery Pack**

incorporates stable nickel-metal hydride (NiMh) power cells and integral protection (required by ATEX) for maximum quality lifespan and safety. A removable fuse protects against short circuit overload and prevents battery damage.

Features

Standard 1100mAh NiMH battery pack for the ToughPIX 2300XP series digital cameras. Incorporates reverse charging and over current protection via replaceable fuse.

- High capacity 1100mAh NiMH cells incorporating inbuilt protection.
- Replaceable short circuit protection fuse.
- Casing manufactured from anodised aluminium.
 - Full UK-based support.

Specifications	
Part No	CDX2341-008
Capacity	1100mAh
Voltage	3V nominal
Recharge	DV
For use with	 » ToughPIX 2300XP Series » LaserMETER 3000XP » Centurion XP series

XP Series Replacement Fuse Kit



Description

Pack of 10, fuses to replace the over current protection fuse built into the XP series battery pack.

Features

The XP series battery packs incorporate a matched, replaceable fuse covered by ATEX certification.

- 10 replacement fuses.
- ^m Fuse replacement tool.

Specifications	
Part No (1.5A)	XP-326-121
Part No (1.25A)	XP-326-120
Part No (1A)	XP-326-115
Kit Contains	» 10 matched fuses for CorDEX Battery Packs» Fuse replacement tool
For use with	 » ToughPIX 2300XP Series » LaserMETER 3000XP » Centurion XP series

For more information visit www.cordexinstruments.com





XP Series Power Supply

Description

The CDX2341-130 battery

charger uses multi-stage charging technology to reduce overall charge time whilst providing continuing trickle charge for continuous top-up without battery damage. The XP series battery packs must be charged correctly to avoid protection system activation or cell damage.

Features

- » Multi-stage charging capability.
- » LED indication of charge status.
- » UK, US, EU & AU adapters supplied as standard.

Specifications	
Model	CDX2341-130
Indication	LED
Charge type	Multi-stage
Weight	0.52kg (1.15lb)
For use with	 » ToughPIX 2300XP Series » LaserMETER 3000XP » Centurion XP series

XP Series Battery Fixing Kit



Description

These stainless steel, high strength fixings can be used to replace those supplied to secured the battery to the camera body.

Features

- » 1 complete set of securing screws required to hold the battery pack in place.
- » Removal/replacement tool.

IMPORTANT SAFETY NOTICE: Only remove the CorDEX Battery Packs in a non-hazardous area. Only use CorDEX Instruments fixings to secure the battery to the camera.

Specifications	
Part No	XP-325
Supplied with	» 6 x M4 A2 Stainless steel bolts» Removal/replacement tool
For use with	 » ToughPIX 2300XP Series » LaserMETER 3000XP » Centurion XP series



XP Series Charging Station



Description

All ToughPIX 2300XP series cameras are supplied with a charging station and power supply as standard. Purchase an additional battery pack charging station to charge additional backup batteries (Part No. CDX2341-008).

(Battery NOT included)

Features

- » Single-bay battery charger can be desk or wall mounted.
- » Supplied complete with a power supply and the following adaptors: UK, US, EU & AU.

IMPORTANT SAFETY NOTICE: The battery charger must not be used in a hazardous area. Only use CorDEX Battery Packs. The charging station is not suitable for charging other battery types.

Specifications	
Part No	XP-323
Weight	0.125kg (0.275lb)
Overall dimensions	46 x 93 x 108mm (1.8 x 3.7 x 4.2inches)
For use with	 » ToughPIX 2300XP Series » LaserMETER 3000XP » Centurion XP series

XP Series Leather Harness



Description

The **CorDEX Instruments XP series leather harness** is a safety accessory for when using

your XP series camera at height or for long periods of time.

Specifications	
Model	XP-330
For use with	» ToughPIX 2300XP Series» Centurion XP series



XP Series Replacement USB Plug



Description

The CorDEX XP Series USB

plug is designed for use with the ToughPIX 2300XP Series and Centurion XP series digital cameras. Each camera is supplied as standard with a USB plug.

IMPORTANT SAFETY NOTICE: This product MUST have the USB plug inserted into the camera whilst in Hazardous (potentially explosive) atmospheres. If this plug is not in place the device will not be deemed certified and will leave the end user liable.

Specifications	
Part No	CDX2341-166
For use with	» ToughPIX 2300XP Series» Centurion XP series

XP Series USB Communication Wand



Description

The XP series USB communication wand provides high speed USB communication and has been tested to operate effectively with XP Series Digital Cameras.

IMPORTANT SAFETY NOTICE: Only communicate with a XP digital camera in a non-hazardous area.

Specifications	
Part No	XP-322
Weight	0.23kg (0.51lb)
Length	60cm (23.6in)
For use with	» ToughPIX 2300XP Series» Centurion XP series



XP Series - Optical accessory kit



Description

The XP Series Optical Accessory Kit extends the capability of the standard camera by offering both a close up (macro) lens able to focus 50mm-100mm from an object and a 45 Degree Wide Angle lens.

The macro lens enables crystal clear images of small objects such as serial numbers or rating plates and the wide angle lens offers a single image view of large scenes from restricted areas such as offshore platforms.

Features

- » Capture crystal clear digital images at distances of between 50mm-100mm with the macro lens.
- » Wide-angle lens increases the camera's angle of view by 0.45 times.
- » Features a low intensity certified LED lamp designed for both close up images and movie capture.

Specifications	
Part No	XP-350
Macro lens Specification	37mm combination macro
Wide-angle lens Specification	0.45 wide angle lens AF
For use with	» ToughPIX 2300XP Series» Centurion XP series

XP Series Leather Holster



Description

The **CorDEX Instruments XP** series leather holster is a design that allows you to support the full weight of your camera in a protective cover, and is ideal for carrying your camera whilst on site.

Specifications	
Model	XP-330
For use with	ToughPIX 2300XP Series / Centurion XP Series



Ultrasonic Couplant Gel



Description

CorDEX couplant is designed for use with the UT5000 on all types of metallic surface and is especially suited to solving the problems of rough, pitted, uneven surfaces to allow smooth probe movement during testing.

IMPORTANT SAFETY NOTICE: This product will have a flash point of 160°C (PM) when used for long periods at elevated temperatures.

Specifications	
Part No	XP-560
Size	2 x 125ml (applicator bottles)
Frequency	13.56Mhz
For use with	» UT5000



ATEX Certified RFID Tags

Description

13.56Mhz RFID tags (Radio Frequency Identification) are supplied to be used in connection with the UT5000, intrinsically safe thickness gauge.

Features

- » ATEX Certified II 2G EEx ia IIC T4.
- » ATEX Certified I M2 EEx ia I.
- » ATEX Certified II 2 D Ex iaD 21 T70.
- » IP67 design.

Specifications	
Part No (10x RFID Tags)	XP-510
Part No (50x RFID Tags)	XP-550
Size	34mm
Frequency	13.56Mhz
For use with	» UT5000



Spare Dual Element Transducer



Description

The CorDEX Instruments twin crystal compression wave transducer is suitable for use on >> 1.8m lead. corroded and pitted surfaces, thickness measurement testing with a very low cross-talk.

Features

- » Certified for Zone 1 IIC T4.
- » Dual Element transducer.

Specifications	
Part No	XP-570
Transducer Type	Dual Element Transducer
For use with	» UT5000

Refresh Kit



Description


CorDEX Refresh Kit designed for the UT5000, is a kit designed to help refresh worn and used parts of your UT5000 from wear and tear.

IMPORTANT SAFETY NOTICE: Battery Cover must be in place whilst using the UT5000 in a hazardous area.

Specifications	
Part No	XP-590
Kit contains	 » Shock Resistant Skin » 2 x Wrist strap » Battery Cover » Stand
For use with	» UT5000



CorDEX CONNECT[™] Predictive Maintenance System



Description

CorDEX CONNECT™ software integrates RFID technology, reporting software, and a handheld intrinsically safe thickness gauge to enable predictive maintenance for pipelines and fixed equipment in hazardous areas.

Features

- » RFID tags link measurements to a location, date and time.
- » Make informed predictive maintenance decisions from regular scans.
- » Create full reports and graphs for analysis and trending.
- » Set alarms to highlight serious thinning and corrosion.
- » Real time firmware updates and calibration tracking.
- » Copy included with every UT5000.

System Requirements			
Windows Version	Minimum	Recommended	
ХР	512MB RAM	1024MB RAM	
Vista, 7	1024MB RAM	2048MB RAM	
Requires Adobe Reader to view the reports created.			

CAMS CorDEX Asset Management Software



Description

CAMS – Asset Management Software allows users to manage, annotate and generate analytical reports with the images taken from a CorDEX Instruments explosion proof digital cameras quickly and easily.

Features

- » Organise, edit and annotate images.
- » Produce detailed reports in a few easy steps.
- » Highlight problem severity levels.
- » Create albums to store and organize your photos.
- » Receive latest updates from CorDEX Instruments.
- » Copy included with every ToughPIX digital Camera.

System Requirements			
Windows Version	Minimum	Recommended	
ХР	512MB RAM	1024MB RAM	
Vista, 7	1024MB RAM	2048MB RAM	
Requires Adobe Reader to view the reports created.			



18



WWW.CABLEJOINTS.CO.UK THORNE & DERRICK UK TEL 0044 191 490 1547 FAX 0044 477 5371 TEL 0044 117 977 4647 FAX 0044 977 5582 WWW.THORNEANDDERRICK.CO.UK