

## General Description

Craig and Derricott have been manufacturing flush mounting isolators for more than 20 years and in that time the design has been carefully modified to give features that installers and end users really need.

The assembly consists of a galvanised back box (complete with knockouts) and stainless steel fascia plate which carries the isolating switch and lockable handle. The fascia plate now comes in an attractive brushed finish which resists the fingerprint effect associated with highly polished surfaces.

Equally at home in kitchens, laboratories, food processing areas, hospitals and many other areas where an elegant, low projection isolation device is required.



## **i** Safety Features

### Padlocking

All items allow the insertion of up to three padlocks in the 'Off' position.

It is recommended that padlocking devices with a standard hasp diameter of 6.4mm are used. This will lock the handle in the 'Off' position. (Handles lockable in the 'On' position are available to special order.)



### Security

The fixing screws that secure the lid to the back box are supplied with allen key heads to give a degree of security. Fixings with a higher degree of security can be supplied to order.

Switch Disconnectors (O-I) —/—

## Catalogue Numbers

Rating	Format	Interior Switch Product Range	Cat. No.	Enclosure Size *
20A	2P	GX	SDFL252	A
	3P		SDFL253	
	4P		SDFL254	
40A	2P	GX	SDFL402	B
	3P		SDFL403	
	4P		SDFL404	
63A	2P	GN	SDFL632	C
	3P		SDFL633	
	4P		SDFL634	

\*

